

FIRST RE-ESTABLISHMENT

GCDB 340500

Quarter corner common to Sections 9 and 16, Township 34 South, Range 1 West, W.M.

Found flush in ring of stone, the 3/4-inch diameter iron pin, with attached 2½-inch diameter brass cap marked:

T34S R1W
S9
¼S —
S16
RANGES 483 1967

Set on Survey No. 3495, dated 1967.

Added the marks "C.S. 1988" to said brass cap.

Original bearing trees recorded by Ives and Hyde in 1854 found:

- The root crown of a down White Oak, 22-inch diameter with sawed and/or rotted out faces, bears Record: N67°E, 21.12 feet to estimated position of original face. The above noted survey describes this tree, in 1967, as having "scribing intact".
- White Oak, 36-inch diameter with axed and/or rotted-out faces bears Record: S51°W, 58.74 feet to estimated position of original face. Re-measured 59.74 feet to center of tree at base.

Mark new trees "CS" "BT" and take measurements to center of trees at lower blaze:

- White Oak, 8-inch diameter, bears N69°15'E, 42.05 feet.
- White Oak, 6-inch diameter, bears S28°15`W, 11.90 feet.

Corner lies at west edge of shale rocked private road (Conner Lane) c. north-south, about 20½ feet Southerly of the inlet end of a 12-inch diameter C.M.P.

August 31, 1988
R. Frost, Tech.
S. Beecher, Tech.

Edward McGinty
County Surveyor

V = 18½°
P.-327