

PROPORTIONED CORNER
GCDB 400240

Quarter corner between Section 27 & 28, Township 34 South, Range 1 West.

All original evidence destroyed.

Re-established corner by running from the corner of Section 21, 22, 27, 28 to the corner of Section 27, 28, 33 and 34. At point midway between said corners drove iron pin for corner.

From which:

- A 10" B.O. bears N51°E, 24.00 feet.
- A 14" B.O. bears N52°W, 19.04 feet.

June 11, 1917
A.T. Brown
County Surveyor

Ed Dutton, Chainman
Grant Matthews, Chainman

SEE NEXT PAGE FOR NEXT RENEWAL

PROPORTIONED CORNER

GCDB 400240

Quarter corner between Sections 27 and 28, Township 34 South, Range 1 West.

No evidence of the original corner.

Set a 1"x 22" sharpened iron pin flush with the paving midway and on line between the first section corner North and South for corner

From which

- A 14" White Oak scribed CS-BT bears North $66\frac{1}{4}^{\circ}$ East, 28.4 feet,
- scribe a 22" Laurel CS-BT which bears South 35° East, 50.7 feet.

November 6, 1952
C. Z. Boyden
C.L. Birk

(See Corners Endangered by Construction Book)

SEE NEXT PAGE FOR FIRST RE-ESTABLISHMENT

SPECIAL CORNER

FIRST RE-ESTABLISHMENT

GCDB 400240

Quarter corner common to Section 27 and 28, Township 34 South, Range 1 West, W.M.

From the following evidence at location described below, set a 1 x 30-inch diameter flanged galvanized iron pipe, set 24 ins. in the ground in concrete, with attached brass cap marked:

T34S R1W

¼S

28 27

REF MON

1994

Jackson County Surveyor

True Quarter Corner falls in State Hwy bears N57°W, 177.43 feet.

Note: All bearing trees marked on first establishment, page 9, dated 1952 are now gone due to State Highway Departmentt new R/W width clearing.

RPs taken in 1993 field book, pages 46 and 134, 5/8 x 24 ins. rebar with aluminum caps marked "Jackson County CS" found:

- Flush, bears N57°W, 470.01 feet.
- Projecting 6 ins., bears S57°E, 24.36 feet.

New bearing trees marked "CS" "BT" and take measurements to the center of tree at lower blaze:

- South fork of a 22-inch diameter Madrone, bears N42°55'E, 27.00 feet.
- Black Oak, 23-inch diameter, bears S18°58'W, 27.56 feet.

Reference monument lies 13 feet east of new State Hwy R/W fence. Set a 5½ feet steel fence post with attached location tag along side of corner.

July 11, 1994
T. Newcomb, Tech.
J. Burgess

Verlyn Thomas
County Surveyor

P.-117