

FIRST RE-ESTABLISHMENT

GCDB 400340

Quarter corner between Sections 21 and 22, Township 34 South, Range 1 West, W.M.

Found original Black Oak BT to Southwest dead with scribe legible. Also stump hole of tree to Northeast together with line tree to North.

From which evidence:

- Set a 1"x 36" galvanized iron pipe 34" in the ground for the corner.

From which:

- A White Oak 14" scribed CS-BT bears South $37\frac{1}{2}^{\circ}$ W 89.65 feet.
- A Fir 12" scribed CS-BT bears North 76° East 64.05 feet.

October 25, 1945
C. Z. Boyden
R. E. Welch
E. Foley

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 400340

Quarter corner common to Sections 21 and 22, Township 34 South, Range 1 West, W.M.

Found the 1" galvanized iron pipe set for corner on the First Re-establishment by Deputy County Surveyor, C. Z. Boyden on October 25, 1945.

From which:

- The 1945 bearing tree (now a 16" White Oak with healed blazes) bears $S37\frac{1}{2}^{\circ}W$, 89.65 feet to the theoretical upper blaze;
- The 1945 bearing tree (now a 13" dead Fir, plainly scribed "CS"BT") bears $N77^{\circ}E$, 64.0 feet to the face.

Marked a new tree as follows:

- A 13" Yellow Pine, scribed "CS-BT" bears $N82^{\circ}E$ 33.3 feet to the face.

December 17, 1969
Otis Blankenship
Phil Blevins

Approved By:
Mark E. Boyden
Jackson County Surveyor

SEE NEXT PAGE FOR THIRD RE-ESTABLISHMENT

THIRD RE-ESTABLISHMENT

GCDB 400340

Quarter corner common to Sections 21 and 22, Township 34 South, Range 1 West, W.M.

Found projecting 4 ins., the 1-inch diameter iron pipe, set on First Re-establishment, page 9, in 1945.

In top of said pipe set a 2½-inch diameter brass cap marked:

T34S R1W
¼S
21 | 22
C.S.
1986

Bearing trees marked on First Re-establishment found and measured to center of tree at lower blaze:

- White Oak, 16-inch diameter, with healed blazes, bears S37½°W, 89.94 feet. Record: 89.65 feet.
- Douglas Fir snag, 14-inch diameter, with scribe marks "CS" "BT" on exposed faces, bears N77°E 64.18 feet. Record: N76°E, 64.05 feet.

Bearing tree marked on Second Re-establishment in 1969 found and measured to center of tree at lower blaze:

- Ponderosa Pine 17-inch diameter, with healed blazes, bears Record: N82°E, 33.30 feet.

Marked new tree "CS" "BT":

- White Oak 10-inch diameter bears N35°W, 20.80 feet to center of tree at lower blaze.

Corner lies about 180 feet Northeast of small pond. Fence line projects South and West from corner.

September 30, 1986
T. Newcomb
D. Edwards

Edward McGinty
County Surveyor

V = 18°
P.-268