

FIRST RE-ESTABLISHMENT

GCDB 400500

Corner to Sections 9, 10, 15 and 16, Township 34 South, Range 1 West.

Found mound of stone and three original BTs.

Set 2" x 36" galvanized pipe for corner.

From which

- The original white oak BT bears N.49°15'E., 17.8 feet.
- The original white oak BT bears N.85°30'W., 13.9 feet.
- The original BT bears S.23°45'W., 33.0 feet.
- A 6" white oak scribed C.S.-BT bears S.34°30'E, 50.7 feet.

February 18, 1929
Boyden, Deputy County Surveyor

Tice and E. H. Judd, Chainmen

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 400500

Section corner to Sections 9, 10, 15 and 16, Township 34 South, Range 1 West.

Found the 2" galvanized iron pipe corner monument with top 10" above the ground surface with the Northeast, Northwest and Southwest original White Oak witness trees in place, but badly rotted.

From said pipe corner, I take new witness trees as follows:

- An 8" White Oak, scribed "CS-BT" which bears North 84° West, 60.2 feet;
- A 10" White Oak, scribed "CS-BT" which bears South 26½° West, 42.2 feet;
- A 12" White Oak, scribed "CS-BT" which bears North 38½° East, 85.0 feet.

August 24, 1955

M. E. Boyden

L. D. Berntson

SEE NEXT PAGE FOR THIRD RE-ESTABLISHMENT

THIRD RE-ESTABLISHMENT

GCDB 400500

Corner common to Sections 9, 10, 15 and 16 Township 34 South, Range 1 West, W.M.

Found the 2" galvanized iron pipe exposed 10" as set for the corner on First Re-establishment by Deputy County Surveyor C. Z. Boyden on February 18, 1929.

Replaced said pipe with a 1" x 10" galvanized iron pipe with a 2½" bronze cap set in concrete with cap 11" below the ground surface. Cap stamped:

	T34S	R1W	
	9	10	
Sec.			Cor.
	16	15	
	C.S.		
	1971		

From which:

- The original bearing tree, (now a 28" White Oak with upper face open and rotted) bears N49¼°E, 18.6 feet to the center (original Record: 20" White Oak N48°E, 17.82 feet) (1929 re-establishment N49°15'E, 17.8 feet)
- The original bearing tree, (now a burnt out White Oak stump) bears N86°W, 14.2 feet to the center (original Record: 18" White Oak, N85°W 13.86 feet) (1929 re-establishment: N85°30'W, 13.9 feet).
- The bearing tree established on said 1929 re-establishment, (now a 12" White Oak with healed blazes) bears S34½°E, 51.0 feet to the center (1929 re-establishment: 6" White Oak S34°30'E, 50.7 feet).
- The bearing tree established on the Second Re-establishment by Deputy County Surveyor, Mark E. Boyden on August 24, 1955, (now an 11" White Oak with healed blazes) bears N84°W, 60.8 feet to the center (1955 re-establishment: 8" White Oak N84°W, 60.2 feet).
- The bearing tree established on said 1955 re-establishment, (now a 17" White Oak with partially healed blazes) bears N38½°E, 85.1 feet to the face of the upper blaze (1955 re-establishment 12" White Oak N38½°E, 85.0 feet).

Mark new tree as follows:

- A 12" White Oak scribed "CS-BT" bears S50¼°W 68.3 feet to the face of the lower blaze.

November 16, 1971
Gary Kaiser,
Deputy County Surveyor

Lloyd Shreeve

SEE NEXT PAGE FOR FOURTH RE-ESTABLISHMENT

FOURTH RE-ESTABLISHMENT

GCDB 400500

Corner common to Sections 9, 10, 15 and 16 Township 34 South, Range 1 West, W.M.

Monument set on Third Re-Establishment in 1971 was not found, apparently destroyed by construction. From remaining evidence, reset new monument in original location.

Set a 1" x 36" galvanized iron pipe in mound of stone, with a 2½" brass cap marked:

T34S R1W	
9	10
16	15
C.S.	
2017	

From which:

- Bearing tree marked on the First Re-establishment, dated 1929, and remeasured in 1971: White Oak 14 ins. diameter with healed blazes, brs. S34°45'40"E, 51.06 ft. to center of tree at base. 1971 record S34½°E, 51.0 ft.
- Bearing tree marked in 1971: White Oak 12 ins. diam. with healed blazes, brs. record S50¼°W, 68.3 ft. to estimated face of lower blaze re-measure 68.70 ft. to center of tree at base. (Used as basis of bearing.)

Take new References:

- Found Orange Plastic Cap, marked: "B. Kaiser RLS 52923" , set on filed Survey No. 20660 dated 2010, brs. N00°59'11"W, 25.03 ft. Said cap sits 0.3 ft. south of wire fencing, running E-W and N.
- Set ⅝ ins. diameter rebar with 2 ins. diameter aluminum cap marked: "Jackson County Surveyor" brs. N 80°06'02" E, 50.02 ft. Cap is 8 ft. west and 6 ft. south of corner post (t-post) at SE corner of wire fence.

Corner lies on fill area south of Residence 376 Schoolhouse Ln, approximately 25 ft. south of E-W fenceline.

September 21, 2017
B. Paull
J. Hall

Scott D. Fein
Jackson County Surveyor

.P-