

FIRST RE-ESTABLISHMENT

GCDB 400600

Section corner common to Sections 3, 4, 9 and 10, Township 34 South, Range 1 West, W.M.

Found

- 24" White Oak to Southeast with scribe marks,
- 12" White Oak to Southwest with old axe marks,
- 26" White Oak to Northeast (hollow, no scribe)
- and the stump hole to the Northwest;

From which:

- Set a 3" x 12" x 12" basalt stone with cross on top 2" below the surface of the ground for corner.

From which:

- A 12" White Oak scribed CS-BT bears South $71\frac{1}{4}^{\circ}$ West, 78.5 feet.
- An 8" White Oak scribed CS-BT bears North 75° West, 68.4 feet.
- An 8" White Oak scribed CS-BT bears North $23\frac{1}{2}^{\circ}$ East, 112.4 feet;
- A 16" White Oak scribed CS-BT bears South $42\frac{1}{4}^{\circ}$ East, 88.7 feet.

November 23, 1949

C. Z. Boyden

L. D. Pinkham

M. E. Boyden

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 400600

Because of road construction in this area, found the stone corner as reported in the First Re-establishment by Deputy County Surveyor C. Z. Boyden on November 23, 1949, and replaced same with a 1"x 28" galvanized iron pipe with bronze cap stamped:

	T34S R1W	
	4	3
Sec.		Cor.
	9	10
	c.s.	
	1966	

No new bearing trees were established, however, the 8" White Oak reported as bearing South 75° West, 68.4 feet, actually bears North 75° West, 68.4 feet.

September 22, 1966
Gary Kaiser
Gerald Nygren

Approved By:
Mark E. Boyden
County Surveyor


SEE NEXT PAGE FOR THIRD RE-ESTABLISHMENT

THIRD RE-ESTABLISHMENT

GCDB 400600

Section corner common to Sections 3, 4, 9 and 10, Township 34 South, Range 1 West, W.M.

At the corner, found 14 ins. deep, the 2½-inch diameter brass cap, marked:



As recorded on Second Re-establishment, page 14, in 1966.

Bearing trees recorded on First Re-establishment, page 10, in 1949, found and re-measured to center of trees at lower blaze:

- White Oak, 11-inch diameter with healed blazes, bears N23°30'E, 113.25 feet. Record: 112.4 feet.
- Sawed White Oak stump, 16 ins., bears S42¼°E, 89.17 feet. Record: 88.7 feet.
- White Oak, 13-inch diameter, bears S71°20'W, 78.80 feet. Record: S71¼°W, 78.5 feet.
- White Oak, 12-inch diameter, with healed blazes, bears N75°W, 68.55 feet. Record: 68.4 feet.

Mark a new tree "CS" "BT":

- White Oak, 11-inch diameter, bears S52°42'E, 95.3 feet to center of tree at lower blaze.

Corner lies about 26 feet, S45°E of gravel road and 51.1 feet, S85½°W, of Power Pole No. A-3798.

December 28, 1983
R. Frost
R. Templin

Edward McGinty
County Surveyor

V = 18°