

GCDB 400640

Corner to Section 3 and 4, Township 34 South, Range 1 West.

Set iron pin for corner.

From which:

- A 14" yellow pine scribed C.S.-BT bears N.40°W. 48.0 feet.
- A 12" yellow pine scribed C.S.-BT bears S.41°E. 62.0 feet.
- A 14" black oak scribed C.S.-BT bears S.05°W. 68.2 feet.
- An 8" black oak scribed C.S.-BT bears N.61°45°E. 77.6 feet.

SEE RECORDED SURVEY NO. 4814

SPECIAL CORNER

FIRST RE-ESTABLISHMENT

GCDB 400640

Quarter corner common to Sections 3 and 4, Township 34 South, Range 1 West, W.M.

Found the 5/8 ins. iron pin, set at proportionate distance in 1970 on Survey No. 4406, protruding 1 inch above the ground. Set a yellow plastic cap marked "Jackson C.S." over found pin.

Bearing tree mentioned as possibly original on Survey No. 4406 found:

- Black Oak, 27-inch diameter with chopped out and totally mutilated faces, bears (1970 record) S33°E, 15.8 feet to estimated face.

Bearing trees marked on Survey No. 4406 found:

- Douglas Fir stump, 13-inch diameter, with scribed "T" visible bears S29°W, 13.7 feet. Record: 29½°W, 14.5 feet to center of stump at lower blaze.
- Douglas Fir stump, 10-inch diameter, with scribed "BT" visible bears Record: N49½°W, 8.5 feet to lower face.

To perpetuate this position, mark new trees "CS" "BT" and measure to center of trees at base:

- White Oak, 7-inch diameter bears N60¼°E, 24.52 feet.
- Incense Cedar, 6-inch diameter, bears S24¼°W, 44.54 feet.

Corner lies 20 feet West of power line and 15 feet South of dirt road, alongside a 12-inch diameter Yew fence post.

August 27, 1987
S. Beecher, Tech.
R. Frost, Tech.

Edward McGinty
County Surveyor

V = 18½°
P.-320

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SPECIAL CORNER

SECOND RE-ESTABLISHMENT

GCDB 400640

Quarter corner common to Sections 3 and 4, Township 34 South, Range 1 West, W.M.

Found the 5/8-inch diameter iron pin projecting 1 ins. set on Survey No. 4406, dated 1970, with a yellow plastic cap marked "Jackson CS" set on First Re-establishment, dated 1987.

Over found pin set a 1 1/4 x 26-inch diameter galvanized iron pipe 24 ins. in the ground, with a 2 1/2-inch diameter brass cap marked:

T34S R1W
1/4S
4 | 3
CS
1994

Due to road construction, all bearing trees destroyed except the bearing tree marked on First Re-establishment a White Oak 7-inch diameter, with healed blazes, bears S59°49'W, 24.42 feet to center of tree at lower blaze. Record: N60 1/4 °E, 24.52 feet.

Found projecting 4 ins., a 5/8-inch diameter rebar with yellow plastic cap marked "Kaiser" bears S0°28'30"E, 50.09 feet. Record: 50.00 feet (Survey No. 13148, dated 1992)

New references taken:

- White Oak, 7-inch diameter, marked "CS" "BT" bears N69°59'W, 21.28 feet to the center of tree at lower blaze.
- Power Pole No. A1973, bears S27°32'W, 62.14 feet.

Corner lies between two roads, North 28 feet and South 15 feet to center of dirt roads.

July 19, 1994
T. Newcomb, Tech.
J. Burgess, Tech.

Verlyn Thomas
County Surveyor

P.-122