

FIRST RE-ESTABLISHMENT

GCDB 500100

Section corner common to Section 34 and 35, Twp. 34 South, Range 1 West, and Section 2 and 3, Twp. 35 South, Range 1 West, W.M.

From the following evidence, at the location described below, I set a 1x36-inch G.I. pipe, 30 ins. in the ground with a 2½ ins. bronze disc marked:

Jackson County 1978	
T34S	R1W
34	35

3	2
T35S	

Original bearing trees recorded by Ives and Hyde in 1854 found as follows:

- Burned out black oak stump shell about 18-inch diameter containing old axe work at record location of NE BT.
- The base and stump hole of a down pine, 10-inch diameter with exposed and burned faces, bears Record: S25°E, 20.46 feet.
- Fir snag, 29-inch diameter, with axed and/or burned out faces, bears Record: S33°W, 11.88 feet to burned upper face.
- Black Oak, 20-inch diameter with opened faces, (rotted inside) bears Record: N38°W, 26.40 feet, on slope.

I mound stones around corner mark new trees CS BT and take measurements to center of trees at lower blazes:

- Douglas fir, 8-inch diameter, bears N60½°E, 36.44 feet.
- Laurel, 6-inch diameter, bears S50°E, 25.15 feet.
- Laurel, 9-inch diameter, bears S42°W, 14.92 feet.
- White oak, 16-inch diameter, bears N33°W, 33.42 feet.

Corner lies 4 feet North of E-W (page wire) fence and about 35 feet West of creek.

B. Malotte
R. Frost
January 3, 1978

Approved by: Edward McGinty
County Surveyor