

FIRST RE-ESTABLISHMENT

GCDB 500600

Corner to Sections 2, 3, 10 and 11, Township 34 South, Range 1 West.

Set a 2" x 36" galvanized iron pipe with top 8" above the ground surface for corner from which,

- The original witness tree (now a 36" Yellow Pine) with scribe marks legible bears South 49° West, 27.04 feet.
- The original witness tree (now a 10" Black Oak) with scribe marks legible, but in poor condition, bears North 17° East, 49.2 feet.

I scribe new trees as follows:

- A 12" Douglas Fir "CS-BT" bears North 59° East, 45.9 feet;
- A 6" Laurel "CS-BT" bears North 58° West 14.6 feet;
- A 5" Black Oak "CS-BT" bears South 19° East 55.4 feet.

June 29, 1957
M. E. Boyden
E. H. Hedrick

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 500600

Section corner common to Sections 2, 3, 10 and 11, Township 34 South, Range 1 West, W.M.

Found projecting 6 ins., the 2-inch diameter iron pipe, set on First Re-establishment dated 1957. In the top of said pipe set a 2½-inch diameter brass cap marked:

T34S	R1W
3	2
10	11
CS	
1991	

The single remaining original bearing tree recorded by Ives and Hyde in 1854, now a broken off Ponderosa Pine stump 38-inch diameter, with visible scribe marks "R1W T34S S10" on exposed face bears S48°W, 29.04 feet to face. Record: S49°W, 1957 record 27.04

Bearing trees marked on First Re-establishment found with healed blazes and measured to center of tree at lower blaze:

- Douglas Fir, 18-inch diameter, bears N59°E, 46.35 feet. Record: 45.90 feet.
- White Oak, 7-inch diameter, bears Record: S19°E, 55.40 feet
- Madrone, 8-inch diameter, bears N58½°W, 15.00 feet. Record: N58°W, 14.60 feet.

Marked new tree "CS" "BT":

- Ponderosa Pine, 8-inch diameter, bears S7½°W, 58.80 feet to the center of tree at lower blaze.

Corner lies on small level area, S48°W, 40 feet from corner of steep descent.

October 8, 1991
T. Newcomb, Tech.
H. Durkee, Tech.

Verlyn Thomas
County Surveyor

V = 17°
p.-73