

## FIRST RE-ESTABLISHMENT

GCDB 500640

One-Quarter corner common to Sections 2 and 3, Township 34 South, Range 1 West, W.M.  
 $V = 15^\circ$

The original survey that was executed by Ives and Hyde in 1854 was in error as to the distance to the reference tree(s). Due to this error I set a  $\frac{3}{4}$  x 13 ins. re-steel rod projecting 7 ins. with a  $2\frac{1}{2}$ -inch diameter bronze disc marked:

JACKSON COUNTY 1979  
T34S R1W  
3 | 2  
 $\frac{1}{4}$ S

At a prorated distance and at bearing intersect.

- I find the original bearing trees, a Black Oak, now 18-inch diameter with partial "4" and "S" reverse scribe visible in opened upper reverse face bears  $N32^\circ E$ , 57.30 feet to face. Record:  $N32^\circ E$ , 55.44 feet.
- A rotted Black Oak stump, approximately 20 inches diameter with old axe marks bears  $S29^\circ W$ , 57.30 feet to estimated face. Record:  $S29^\circ W$ , 55.44 feet.

I mark the following trees "CS" "BT" and take measurements to center of trees at lower blaze:

- Ponderosa Pine, 14-inch diameter, bears  $N16\frac{1}{2}^\circ W$ , 51.8 feet.
- Black Oak, 20-inch diameter bears  $N48\frac{1}{2}^\circ E$ , 55.31 feet.
- I find a bridge spike in ring of stone with  $\frac{3}{4}$  x 23 inches pinched top G.I. pipe alongside, bears  $S75\frac{1}{2}^\circ W$ , 3.25 feet from corner.
- I raise a mound of stone around corner which lies in rocky meadow on ridge top.

October 17, 1979  
B. Malotte  
J. Gallegos

Approved by: Edward McGinty  
County Surveyor

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

## SECOND RE-ESTABLISHMENT

GCDB 500640

Quarter corner common to Sections 2 and 3, Township 34 South, Range 1 West, W.M.

At the corner found a hole 2 inches deep in bedrock with a  $\frac{3}{4}$  x 13 ins. long rebar with brass cap missing, laying alongside of mound of stone.

Re-drilled hole 9 inches deep and reset  $\frac{3}{4}$ -inch rebar projecting 4 inches. Over said rebar set a 2 x 9-inch Galvanized iron pipe filled with concrete with a  $2\frac{1}{2}$  ins. brass cap at the top marked:

T34S R1W  
     $\frac{1}{4}$ S  
    3 | 2  
    C.S.  
    1991

Bearing trees marked on First re-establishment, dated 1979 found with partially healed blazes and take measurements to the center of tree at lower blaze:

- Black Oak, 21-inch diameter, bears N48 $\frac{1}{2}$ °E, 55.42 feet. Record: 55.31 feet.
- Ponderosa Pine, 15-inch diameter, bears N16°W, 51.50 feet. Record: N16 $\frac{1}{2}$ °W, 51.80 feet

Mound stones around corner and mark new trees "CS" "BT":

- Ponderosa Pine, 7-inch diameter, bears N22 $\frac{1}{2}$ °E, 26.70 feet to the center of tree at lower blaze

**Note:** Spike and  $\frac{3}{4}$ -inch diameter pipe are lying on the ground.

Corner lies at Northerly end of large opening on a gentle South slope and about 140 feet South of a spur, course West.

April 18, 1991  
T. Newcomb, Tech.

Verlyn Thomas  
County Surveyor

V = 15 $\frac{1}{2}$ °  
P.-29