

FIRST RE-ESTABLISHMENT

GCDB 500700

Section corner common to Sections 34 and 35, Township 33 South, Range 1 West, and Sections 2 and 3, Township 34 South, Range 1 West.

Set a 1"x 36" galvanized iron pipe 20" in the ground with a 2½" brass cap stamped:

T33&34 SR1W	
34	35
Sec.	Cor.
3	2
C.S.	
1967	

From which:

- The original Pine bearing tree now 22" and plainly scribed, bears South 76° West, 32.3 feet, (our official records give this course as North 76° West, however, the tree is scribed "S3" and an early record of the corner also notes the tree as bearing Southwest);
- The original white oak, now 15", bears North 25½° West, 136.4 feet to the face of the upper blaze;
- The original white oak, now 15", bears North 8¾° East 150.9 feet.

Marked the following new trees:

- An 8" White Oak scribed CS-BT bears North 78½° East, 85.7 feet to the face of the lower blaze;
- A 22" Yellow Pine scribed CS-BT bears South 42° East 126.8 feet.

July 24, 1967
F. A. Roberts
J. Huston

Approved By:
L. D. Pinkham,
Deputy County Surveyor

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 500700

Section corner common to Sections 34 and 35 of Township 33 South, and sections 2 and 3 of Township 34 South, Range 1 West, W.M.

Found at corner exposed 12 ins. the 1½ ins. diam. galv. iron pipe with a 2½ ins. diam. brass cap set on 1st Re-establishment in 1967 and marked

T33 & 34S R1W	
34	35
SEC	COR
3	2
C.S.	
1967	

Aluminum post with sign found 3 ft. north.

Original bearing trees recorded by Ives and Hyde of the GLO in 1854 found with healed blazes and measures to center at base:

- P. Pine now dead, down and rotted brs. S76°W, 32.6 ft. record 32.3 ft. to face.
- W. Oak now 15 ins. diam. brs. N25½°W, 136.8 ft. record 136.4 ft. to face.
- W. Oak now 16 ins. diam. brs. N8¾°E, 151.2 ft., record 150.9 ft. to face.

Bearing tree recorded on said 1st Re-establishment found with healed double blazes and measured to center at lower blaze;

- W. Oak now 9 ins. diam. brs. N78½°E, 86.0 ft., record 85.7 ft. to face.
- P. Pine dead, down, and rotted brs. S42°E, 127.4 ft. to center of stump hole, record 126.8 ft. to face.

Marked new bearing trees 'CS' "BT' and measured to center at lower blaze;

- W. Oak 6 ins. diam. brs. East, 89.0 ft.
- W. Oak 7 ins. diam. brs. S62½°W, 41.6 ft.

Corner lies approx. 600 ft. east of bend in private road and approx. 3 ft. south of east-west deteriorated fence.

February 18, 2009

B. Beeman

H. Durkee

Kerry K. Bradshaw
Jackson County Surveyor

P. – 38
V – 15°50'