

## FIRST RE-ESTABLISHMENT

### GCDB 600200

Section corner common to Sections 25, 26, 35, and 36, Township 34 South, Range 1 West, W.M.  
 $V = 20\frac{1}{2}^\circ$

From the following evidence, at the location described below, I set a 1x36-inch G.I. pipe 26 ins. in the ground with a  $2\frac{1}{2}$  ins. bronze disc marked:

Jackson County 1975	
T34S R1W	
26	25
-----	
35	36

Original BTs recorded by Ives and Hyde in 1854, found as follows:

- The rotted and burned stump remains of a Fir, 30ins. diam., scribe "BT", bears record  $N3^\circ E$ , 110.88 feet.
- The stump hole of a down and burned Black Oak (undetermined diam.) bears record  $S53^\circ W$ , 23.76 feet.
- The base of a dead and down Black Oak, about 8-inch diameter, bears record  $N80^\circ W$ , 11.88 feet.
- The S.E. BT is gone.

I mound stones around corner, marked the following trees C.S. BT and take measurements to center of trees at lower blaze:

- A Black Oak, 6-inch diameter, bears  $S54\frac{3}{4}^\circ E$ , 27.74 feet.
- A Black Oak, 6-inch diameter, bears  $S48^\circ W$ , 21.64 feet.
- A Black Oak, 6-inch diameter, bears  $N15^\circ W$ , 42.03 feet.
- The corner of South and East bearing fence lines stands  $N55^\circ W$ , 37.9 feet.

Corner lies on West slope, 21 feet South of East-West fence and about 200 feet West of location marker on 6-inch diameter Black Oak, at top of ridge.

February 25, 1975  
B. Malotte  
R. Frost

Approved by: Edward McGinty  
County Surveyor