

## FIRST RE-ESTABLISHMENT

GCDB 600400

Section corner to Sections 13, 14, 23 and 34, Township 34 South, Range 1 West, W.M.

Found stumps of original BTs. to Southwest and Northwest, plainly scribed, the original BT to Northeast lying on ground, with scribe visible; the stump to original BT to Southwest in place with scribe visible; also stump hole to original BT to Southeast;

From which evidence:

- Set a 2" x 36" galvanized pipe 30" in the ground for corner.

From which:

- A 10" Black Oak, scribed CS-BT bears North  $88\frac{1}{4}^{\circ}$  East, 20.6 feet;
- Scribe a 5" Black Oak CS-BT which bears South  $49\frac{3}{4}^{\circ}$  East, 28.8 feet;
- Scribe a 7" Cedar CS-BT which bears South  $21^{\circ}$  West, 14.35 feet;
- Scribe a 6" White Oak CS-BT which bears North  $37\frac{1}{2}^{\circ}$  West, 39.4 feet.

June 7, 1935  
C. Z. Boyden,  
Deputy County Surveyor  
O. H. Tice, Chainman

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

**SECOND RE-ESTABLISHMENT**

**GCDB 600400**

Section corner common to Sections 13, 14, 23 and 24, Township 34 South, Range 1 West, W.M.

Found at the corner, 2-inch diameter iron pipe projecting 6 ins., set on First Re-establishment, page 7, dated 1935.

In the top of found pipe, set in cement, 2½-inch diameter brass cap marked:

T34S R1W	
14	13
-----	
23	24
C.S.	
1981	

From which:

- Remains of pine stump, approximately 18-inch diameter found at record location of original N.E. BT.

Bearing trees marked on First Re-establishment found and measured to center of trees at lower blaze:

- White Oak (dead), 7-inch diameter with healed blazes bears S49¾°E, 29.10 feet. Record 28.8 feet.
- Cedar, 13-inch diameter with healed blazes bears S20°W, 14.18 feet. Record: S21°W, 14.35 feet.
- White Oak, 12-inch diameter with healed blazes bears N35°W, 38.94 feet. Record: N37½°W, 39.4 feet.

Mark new trees "C.S." "BT" and measure to center of trees at lower blaze:

- Cedar, 9-inch diameter, bears N71°E, 37.00 feet.
- Ponderosa Pine, 7-inch diameter, bears S57°E, 29.65 feet.

Corner lies at the corner of South and East bearing fence lines.

June 22, 1981  
R. Frost  
R. Templin  
Witness: C. McLoughlin

Edward McGinty  
County Surveyor

V = 20°

P.-97