

FIRST RE-ESTABLISHMENT

GCDB 640300

Quarter corner common to Sections 24 and 25, Township 34 South, Range 1 West, W.M. $V = 23^\circ$

In a found mound of stone, I set a 1x36-inch G.I. pipe 26 ins. in the ground with a 2½ ins. bronze disc marked:

Jackson County 1975
T34S R1W
24
¼S —
25

Original BTs recorded by Ives and Hyde in 1854, found as follows:

- The stump remains of a down and decayed Black Oak, bears record $S38^\circ E$, 17.16 feet.
- The stump depression of a down and rotted Pine, 16-inch diameter, scribed "BT" in exposed face, bears record $N32^\circ W$, 8.58 feet.

I marked the following trees C.S. BT and take measurements to center of trees at lower blaze:

- A White Oak, 8-inch diameter, bears $S21^\circ W$, 22.73 feet.
- The center branch, 5-inch diameter, of a multiple Black Oak, bears $N17\frac{1}{2}^\circ W$, 19.80 feet.

An old blazed line runs East from corner, which lies near N.E. corner of a small bench, about 170 feet South of location marker on 4-inch diameter White Oak, alongside Easterly-Westerly fence line.

The top of round knobs visible from corner, bears $N27\frac{1}{2}^\circ E$, about 2,500 feet and $N47^\circ E$, about 3,700 feet distant.

February 11, 1975
B. Malotte
R. Frost

Approved by: Edward McGinty
County Surveyor