

## FIRST RE-ESTABLISHMENT

GCDB 700300

Section corner on Township Line. Corner to Sections 24 and 25, Township 34 South, Range 1 West, W.M.; Corner to Sections 19 and 30, Township 34 South, Range 1 East, W.M.

Found

- Redwood BT to Northwest, (which proved to be a Cedar), dead, but plainly scribed;
- Also original Pine BT to Southeast, dead, scribe legible;
- Also stump hole of Black Oak BT to Northeast;

From which evidence:

Set a 24" x 24" x 12" rock with cross on top for corner, in a rocky draw;

From which,

- A cross within a circle chiseled on top of highest point of a rock cliff 40 feet in length, 15 feet wide and 15 feet high for B.O. bears N.43¼°E. 61.6 feet;
- Scribe an 8" Black Oak C.S.-BT which bears S.74¾°E. 114.2 feet;
- A cross chiseled on a rock 4 feet long, 3 feet wide and 3 feet high for B.O. bears N.76½°W. 58.7 feet;
- Scribe a 20" Black Oak C.S.-BT which bears S.48¼°W. 143.0 feet.

June 5, 1935  
C. Z. Boyden,  
Deputy County Surveyor  
O. H. Tice, Chainman

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

## SECOND RE-ESTABLISHMENT

GCDB 700300

Corner common to Sections 19, 24, 25 and 30, Township 34 South, Range 1 West and 1 East, W.M.

Found the 24" x 24" x 12" stone with cross set for the corner on the First Re-establishment on June 5, 1935.

Replaced stone with a 1"x 36" galvanized iron pipe with 2½" bronze cap and built mound of stone around it. Brass cap is stamped:

T34S,R1W-1E	
24	19
Sec.	Cor.
25	30
C.S.	
1972	

From which:

- The original bearing tree, now a down cedar snag with scribing visible on under side, bears N55½°W, 99.0 feet to center of stump hole. (Original Record: 15" Redwood, N55½°W, 99.0 feet).
- Found cross chiseled on 4 foot long, 3 foot high, 3 foot wide rock on said First Re-establishment, which bears N76½°W, 59.01 feet (First Re-establishment - N76½°W, 58.7 feet)
- Found a cross within a circle chiseled on top of highest point of a rock cliff 40 feet in length, 15 feet wide and 15 feet high on said First Re-establishment, which bears N43¼°E 61.65 feet. (First Re-establishment N43¼°E, 61.6 feet )
- The bearing tree marked on said First Re-establishment, now a 26" Black Oak with two healed faces, bears S48¼°W, 143.9 feet to center.
- (First re-establishment: 20" Black Oak, S48¼°W, 143.0 feet).

Set a concrete nail with shiner on highest point of a rock 5 feet long, 4 feet wide and 4 feet high, which bears: S61¾°E, 38.98 feet.

June 28, 1972  
Lloyd Shreeve  
Ray Webber

Approved By:  
Gary D. Kaiser,  
Deputy County Surveyor

**SEE NEXT PAGE FOR THIRD RE-ESTABLISHMENT**

### THIRD RE-ESTABLISHMENT

GCDB 700300

Section corner common to Sections 24 and 25, Township 34 South, Range 1 West and Sections 19 and 30, Township 34 South, Range 1 East, W.M.

Found projecting 20 ins. from mound of stones, the 1-inch diameter galvanized iron pipe, with a 2½-inch diameter brass cap marked:

T34S R1W-1E	
24	19
— —	
25	30
C.S.	
1972	

As recorded on Second Re-establishment, page 22 in 1972.

Remaining references, reported on Second Re-establishment, recovered and re-measured as follows:

- Concrete nail in metal disc atop large rock, bears S60°39'E, 38.98 feet. Record: S61¾°E.
- Chiseled across atop large rock, bears N75°33'W, 59.01 feet. Record: N76½°W.

Mound (add) stones, flush to brass cap, mk. new trees "CS" "BT" and take measurements to center of trees at lower blaze:

- Ponderosa Pine, 11-inch diameter, bears N20°22'E, 98.0 feet.
- Douglas Fir, 10-inch diameter, bears S43°02'W, 103.9 feet.

Corner lies in boulder strewn draw, c. S20°W, about 40 feet North of old abandoned road (near culvert outlet) and an estimated 300 feet North of jeep road at foot of hill alongside creek. See also Jackson County Project File 86-67.

October 15, 1986  
R. Frost  
T. Newcomb  
D. Edwards

Edward McGinty  
County Surveyor

P.-285