

## FIRST RE-ESTABLISHMENT

GCDB 700440

Quarter corner common to Section 13, Range 1 West, and Section 18, Range 1 East, Township 34 South, W.M.  $V = 20^\circ$

From the following evidence at the location described below, I set a 1x36-inch G.I. pipe 26 ins. in the ground with a 2½ ins. bronze disc marked:

Jackson County 1975  
T34S  
¼S  
13 | 18  
R1W R1E

Original BTs recorded by Ives and Hyde in 1854, found as follows:

- A White Oak, 12-inch diameter, containing reverse impression of chain notch and scribed "B" in opened lower face, bears record  $S77^\circ E$ , 18.48 feet to scribed face.
- The stump remains of a White Oak, with fragments of axed face in evidence alongside bears Record:  $S66^\circ W$ , 23.10 feet.

I mound stones around corner, marked new trees C.S. BT and take measurements to center of trees at lower blaze:

- Douglas Fir, 8-inch diameter, bears  $N77^\circ E$ , 5.45 feet.
- Cedar, 6-inch diameter, bears  $N12^\circ W$ , 24.87 feet.

Corner lies on small ridge near head of draw.

May 27, 1975

B. Malotte

R. Frost

Approved by: Edward McGinty  
County Surveyor