

FIRST RE-ESTABLISHMENT

GCDB 700540

Quarter corner common to Section 12, Range 1 West, and Section 7, Range 1 East, Township 34 South, W.M. $V=21^\circ$

From the following evidence at the location described below, I set a 1x36-inch G.I. pipe 26 ins. in the ground with a $2\frac{1}{2}$ ins. bronze disc marked:

Jackson County 1975
T34S
 $\frac{1}{4}$ S
12|7
R1W R1E

Original BTs recorded by Ives and Hyde in 1854, found as follows;

- A White Oak, 8-inch diameter, scribed " $\frac{1}{4}$ S" in opened face, bears record N 57° E, 17.82 feet to scribed face.
- A Ponderosa Pine, 29-inch diameter, with healed blazes, bears Record: S 36° W, 62.04 feet (on slope) to estimated face. Re-measured, 61.12 feet to center of tree at lower blaze.

I mound stones around corner and marked a new tree C.S. BT:

- White Oak, 6-inch diameter, bears S $64\frac{1}{2}^\circ$ E, 12.30 feet to center of tree at lower blaze.

Corner lies 100 feet South of the South edge of a small, rocky clearing and about 550 feet South of location marker on 16-inch diameter Fir, alongside road.

May 27, 1975

B. Malotte

R. Frost

Approved by: Edward McGinty
County Surveyor