

FIRST RE-ESTABLISHMENT

GCDB 700600

Section corner common to Section 1 and 12, Range 1 West, and Section 6 and 7, Range 1 East, Township 34 South, W.M. $V = 20\frac{1}{2}^\circ$

From the following evidence, at the location described below, I set a 1x36-inch G.I. pipe 30 ins. in the ground, with a 2½ ins. bronze disc marked:

Jackson County 1975

T34S	
1	6

12	7
R1W	R1E

Original BTs recorded by Ives and Hyde in 1854, found as follows:

- A rotted Yellow Pine stump core bears record, N25°E, 38.94 feet.
- The stump hole of a down and burned Pine about 18-inch diameter bears record S78°E, 77.88 feet on slope.
- A burned Pine snag, now 19-inch diameter scribed "R1W T34S S12" and "BT" in exposed faces, bears Record: S12°W, 45.54 feet to scribed lower face.
- White Oak, 18-inch diameter, with healed blazes, bears record, N18°W, 51.48 feet to center of tree at lower blaze.
- A down Pine snag, found at record location of line tree.

I mound stones around corner, marked new trees C.S. BT and take measurements to center of trees at lower face:

- Ponderosa Pine, 20-inch diameter, bears N59½°E, 76.15 feet.
- Ponderosa Pine, 9-inch diameter, bears S67°E, 48.56 feet.
- Ponderosa Pine, 8-inch diameter, bears S54°W, 31.65 feet.

May 29, 1975

B. Malotte

R. Frost

Approved by: Edward McGinty
County Surveyor