

FIRST RE-ESTABLISHMENT

GCDB 700640

Quarter corner common to Section 1, Range 1 West, and Section 6, Range 1 East, Township 34 South, W.M. $V = 22^\circ$

From the following evidence, at the location described below, I set a 1x36-inch G.I. pipe 18 ins. in the ground with a 2½ inch bronze disc marked:

Jackson County 1975
T34S
¼S
1 | 6
R1W R1E

Original BTs recorded by Ives and Hyde in 1854, found as follows:

- The stump remains of a Black Oak, bears S20°E, 1.32 feet. Record S20°E, 6.60 feet.
- A White Oak stump shell, about 16-inch diameter, with evidence of old axe work in remains alongside, bears N50°W, 6.60 feet. Record N50°W, 1.32 feet.
- **Note:** Apparently distances on the above two BTs were erroneously reversed in original recording.
- The original line tree, now a Douglas Fir snag, 44-inch diameter, 15 feet high, containing old axed blazes, bears record North 22.44 feet to center of tree.

The top of a basalt ledge (Bear Mountain) bears as originally recorded, N73°W, plus 17° (vertical angle).

I mound stones around corner, mark the following trees C.S. BT and take measurements to center of trees at lower blaze:

- Douglas Fir, 5-inch diameter, bears N16°E, 29.30 feet.
- Ponderosa Pine, 9-inch diameter, bears N28°W, 61.20 feet.
- Chiseled "X" in top a 2x2x2 feet high basalt rock outcrop, bears S74°E, 2.70 feet.

May 29, 1975

B. Malotte

R. Frost

Approved by: Edward McGinty
County Surveyor