

## FIRST RE-ESTABLISHMENT

MC\_S15&16

GCDB 400427

South Meander corner on the left bank of Rogue River, between Sections 15 and 16, Township 34 South, Range 1 West.

Found a 1" iron pipe with plug and tack for corner, and the original Southeast bearing tree. Opened the lower blaze of said tree and found a BT scribe.

Although the bearing and distance to the corner does not check exactly with the official record, the discrepancy is less than one link.

Since "Edgewood Park Subdivision" and several tract surveys have been controlled by this location, and in lack of any evidence of the other tree, this location was accepted as the recognized and true location of the corner, and so monumented with a 1"x 36" galvanized iron pipe set 34" in the ground with a 2½" bronze cap stamped:

T34S, R1W  
Meander Corner 16 | 15  
c.s.  
1967

From which:

- The original black oak, now 44" in diameter bears South  $46\frac{1}{2}^\circ$  East, 7.0 feet (record South  $43^\circ$  East, 7.26 feet);
- The center of an 8" white oak not scribed bears South  $65\frac{3}{4}^\circ$  West, 29.4 feet.

March 24, 1967  
Gary Kaiser  
L. D. Pinkham,  
Deputy County Surveyor

Charles Hurst, Present  
Robert Malotte, Present  
William Andrews, Present

**ADDENDUM:** A 14 ins. in diam. concrete base flush with the brass cap was poured around this monument by persons unknown. SMB 12-28-2001.