

FIRST RE-ESTABLISHMENT

GCDB 100100

Corner common to Township 34 and 35 South, Ranges 1 and 2 East.

Found stake in a mound of stone and replaced it with a 1"x 36" galvanized iron pipe set 10" in the ground with a 2½" bronze cap stamped:

	T34-35S R1-2E	
	36 31	
TWP	— —	COR
	1 6	
	C.S.	
	1967	

From which:

- A pine stump hole bears North 56° East, 20.5 feet;
- A pine stump hole bears South 25° East, 86.0 feet;
- A pine stump and down snag plainly scribed bears South 48° West, 27.7 feet to the face of the lower blaze;
- A pine stump hole bears North 81° West, 44.2 feet.

Marked the following new trees:

- A 7" White Oak scribed CS-BT bears South 10° West, 8.6 feet to the face of the lower blaze;
- A 14" Pine scribed CS-BT bears South 27° East, 74.5 feet to the face of the upper blaze;
- A 5" White Oak scribed CS-BT bears North 56° West, 9.9 feet to the face of the lower blaze;
- An 8" Pine scribed CS-BT bears North 19° East, 28.2 feet to the face of the upper Blaze.

November 22, 1967
L. D. Pinkham, Deputy County Surveyor
Gary Kaiser

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 100100

Section corner common to Sec. 36, Twp. 34 South, Range 1 East, Sec. 31 T34S, R2E, Sec. 1, T35S, R1E and Sec. 6, Twp. 35 South, Range 2 East, W.M. $V = 18^\circ$

Found, a 1x36 ins. G.I. pipe standing loosely in a mound of stone. No brass cap found

From the following evidence I set a 1x20 ins. G.I. pipe, exposed 10 ins. with 2½ ins. brass cap marked:

Jackson County 1977
T34S
S36 | S31

R1E S 1 | S 6 R2E
T35S

- A dead 17 ins. diam. ponderosa pine, with scribing visible, bears record S27°E, 74.5 feet to center of tree.
- 7 ins. diam. white oak with 2 healed blazes bears record S10°W, 8.6 feet to face of lower blaze.
- 18 ins. diam. pine stump with scribing visible bears S47½°W, 27.7 feet to face of blaze.
- 7 ins. white oak with scribing visible in 2 partially healed blazes bears N57½°W, 9.9 feet to face of lower blaze.
- 10 ins. ponderosa pine with scribing visible in 2 partially healed blazes bears N18°E, 28.2 feet to face of lower blaze.
- The stump remains of a witness tree bear N82°W, 44.2 feet to center of stump.

I mound stones around the corner, marked the following tree C.S. BT and take measurements to the center of tree at lower blaze:

- White oak, 5 ins. diam., bears S50°E, 29.8 feet.

The corner falls in a Southerly fence line, about 12 feet South of an East-West fence line.

July 21, 1977

R. Roberts

E. Graham

Approved by: Edward McGinty
County Surveyor