

FIRST RE-ESTABLISHMENT

GCDB 100300

Corner to Sections 24 and 25 on Township line. Township 34 South, Range 2 East, W.M.

- Found original BT to Northeast.
- Original BT to Southwest line down, scribe marks legible.

Set 3x3x36 oak stake for corner.

From which:

- A 40" cedar scribed C.S.-BT bears N.8°15'W., 66.0 feet.
- A 16" black oak scribed C.S.-BT bears S.39°30'E., 73.6 feet.
- An 8" red fir scribed C.S.-BT bears S.79°30'W., 37.7 feet.

September 29, 1928
Boyden, Deputy County Surveyor
Tice and Frank Netherlands, Chainmen


SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 100300

Section corner common to Sections 19, 30, Township 34 South, Range 2 East and Sections 24 & 25, Township 34 South, Range 1 East, W.M.

Found an unrecorded 2x26 ins. pipe at corner location. Replace said pipe with a 1x36-inch Galvanized iron pipe 28 ins. in the ground with 2½-inch diameter brass cap marked:



- The original bearing tree marked by Ives and Hyde in 1857, a Black Oak stub 24-inch diameter bears Record: N12°E, 50.82 feet to estimated face.
- Stump depression and Pine remains are found at record Southeast position.

Trees marked on First Re-establishment:

- Black Oak 22-inch diameter with rotted interior and broken top bears S39½°E, 73.6 feet (Record S39°30'E).
- Red Fir 16-inch diameter with scribing visible in exposed face bears S79½°W, 37.95 feet (Record S79°30'W, 37.7 feet.)

Mark new trees "CS" "BT" and measure to center at lower blaze:

- Ponderosa Pine 11-inch diameter bears N48½°E, 3.80 feet.
- Ponderosa Pine 5-inch diameter bears S25°E, 14.90 feet.

Corner lies on level ground at the Southeast corner of current logging operation. Blazed line North, South, and West from corner.

January 16, 1987
R. Romio
T. Newcomb

Edward McGinty
County Surveyor

V = 19°

P.-12