


## FIRST RE-ESTABLISHMENT

### GCDB 100400

Section corner common to Sections 13, 18, 19 and 24, Township 34 South, Ranges 1 and 2 East, W.M.

From the following evidence, at the location described below, set a 1x36-inch Galvanized iron pipe 29 ins. in the ground with a 2½-inch diameter brass cap marked:



The original bearing trees marked by Ives and Hyde in 1857;

- A rotten Pine stob with scribing visible on upper and lower faces bears Record: S51°W, 44.22 feet to lower face.
- Black Oak snag, 16-inch diameter bears N55°W, 52.14 feet to estimated face.(Record: N57°W).
- Stump Hole with pine remains bears Record: N50°E, 54.78 feet.
- The 5/8 ins. iron pin with aluminum cap set by RS461 on Survey No 4618, bears S31°W, .75 feet.

Trees marked on Survey No. 4618:

- White Oak, 6-inch diameter with bark scribing visible, bears S25½°W, 17.6 feet to center of base.
- Ponderosa Pine, 11-inch diameter with partially healed single blaze bears N22°W, 46.15 feet to center at base.
- Ponderosa Pine, 11-inch diameter with partially healed single blaze bears N24°E, 48.45 feet to center at base.
- Ponderosa Pine, 11-inch diameter with partially healed single blaze bears S63°E, 67.10 feet to center at base.

Mound Stones around corner and Mark a new tree "CS" "BT":

- White Oak, 9-inch diameter bears S54°W, 35.85 feet to center at lower blaze.

Corner lies on gentle south slope in area of Whitethorn, small Oak and scattered Pine, 150 feet South of Medco Road. See location poster on North side. Blazed line North and South from corner.

January 16, 1987  
R. Romio  
T. Newcomb

Edward McGinty  
County Surveyor

V = 17°

P.-13