

FIRST RE-ESTABLISHMENT

GCDB 100500

Corner common to Sections 12 and 13, Township 34 South, Range 1 East and Sections 7 and 18, Township 34 South, Range 2 East.

Found a 3" scribed stake for corner and set a 1" x 36" galvanized iron pipe 30" in the ground with a 2½" bronze cap stamped:

	T34SR1&2E		
	12	7	
SEC			COR
	13	18	
	C.S.		
	1967		

From which:

- The center of a 12" Fir snag blazes intact, bears North 7° West, 6.7 feet;
- A 24" Fir snag, plainly scribed and leaning badly, bears South 80° East, 4.8 feet to the center near the lower blaze;
- A 20" fir snag, scribe visible, bears North 68° East 26.4 feet to old face.

Marked the following new trees:

- An 8" Cedar scribed CS-BT bears North 43° East, 36.7 feet to the face of the upper blaze;
- A 30" Yellow Pine scribed CS-BT bears South 14° West, 29.9 feet to the face of the lower blaze;
- A 12" Fir scribed CS-BT bears North 62° West 24.4 feet to the face of the upper blaze.

September 15, 1967
Gary Kaiser
L. D. Pinkham,
Deputy County Surveyor

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 100500

Section corner common to Sections 12 and 13 of Township 34 South, Range 1 East, and Sections 7 and 18 of Township 34 South, Range 2 East, W.M.

Found at corner position exposed 8 ins. in a mound of stones, the 1 in. diam. galv. iron pipe with a 2½ ins. diam. brass cap on 1st re-establishment in 1967 and marked:

T34S R1&2E
12 | 7
Sec. ——— Cor.
13 | 18
C.S.
1967

Original bearing trees recorded by Ives and Hyde of the GLO in 1854 found and measured to center of stump holes:

- Fir dead and down and rotted brs. record N7°W, 6.7 ft.
- Fir dead and down and rotted brs. record S80°E, 4.8 ft.
- Fir dead and down and rotted brs. record N68°E, 26.4 ft.

Bearing tree recorded on 1st re-establishment found with healed double blazes and measured to center at lower blaze;

- Cedar snag brs. N43°E, 37.0 ft.; record 36.7 ft. to face.
- P. pine sawed stump brs. record S14°W, 29.9 ft.
- D. fir snag brs. N62°W, 24.9 ft.; record 24.4 ft. to face.

Marked new bearing trees 'CS' 'BT' and measured to center at lower blaze;

- W. oak 10 ins. diam. brs. N71°W, 42.4 ft.
- D. fir 9 ins. diam. brs. N35½°E, 13.9 ft.
- D. fir 6 ins. diam. brs. S39¼°E, 12.5 ft.
- D. fir 9 ins. diam. brs. S45¼°W, 13.9 ft.

Corner lies approx. 500 ft. south from gravel spur and approx. 150 ft. south of creek course westerly

April 13, 2009

B. Beeman

H. Durkee

Kerry K. Bradshaw

Jackson County Surveyor

P. – 79

V. – 14°30'