

FIRST RE-ESTABLISHMENT

GCDB 200100

Section corner on township line - Sections 31 & 32 Township 34 South, Range 2 East - Sections 5 & 6 Township 35 South, Range 2 East.

Found

- The original Black Oak bearing tree to the northeast down with scribe legible,
- The Oak bearing tree to the southeast with a portion of two scribe marks visible,
- Also oak stumps to the southwest and northwest

From which evidence

- Set a 2"x36" iron pipe 30" in the ground for corner

From which:

- An 8" fir scribed CS-BT bears N50½°West, 16.4 feet;
- Scribe an 8" fir CS-BT which bears S53½°W, 40.8 feet;
- Scribe a 12" fir CS-BT which bears S34°E, 31.5 feet;
- Scribe a 5" cedar CS-BT which bears N36°E, 38.4 feet.

April 9, 1954
C. Z. Boyden
L. D. Pinkham
M. E. Boyden

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 200100

Section corner common to Sections 5 and 6, Township 35 South, Range 2 East and Sections 31 and 32, Township 34 South, Range 2 East, W.M.

Found projecting 4 ins., the 2 ins. diam. iron pipe, set on first re-establishment, page 2, in 1954. In the top of found pipe set a 2½ ins. diam. brass cap marked:

T34S	R2E
31	32
6	5
T35S	
C.S.	
1987	

Original bearing trees recorded by N. Ford in 1855 found:

- The base of a down black oak, about 24 ins. diam., containing scribe marks brs. Record: N52°E, 82.5 feet.
- Black Oak, 10 ins. diam. and partly rotted brs. Record: S30°E, 13.86 feet to estimated face.

Bearing trees marked in 1954 found:

- Cedar, 12 ins. diam., with healed blazes, brs. N35¾°E, 38.45 feet to center of tree at lower blaze. Record: N36°E, 38.4 feet.
- Sawed fir stump, 16 ins. diam., brs. Record: S34°E, 31.5 feet to evidence of lower face.
- Fir snag, 10 ins. diam., with healed blazes, brs. Record: S53½°W, 40.8 feet to estimated face.
- Fir, 17 ins. diam., containing scribe marks in partly exposed upper face, brs. Record: N50½°W, 16.4 feet to scribed face. Re-measured, 17.15 feet to center of tree at lower blaze.

Mark new trees "CS" "BT" and take measurements to center of trees at lower blaze:

- Sugar Pine, 20 ins. diam., brs. S15½°E, 39.95 feet.
- Cedar, 5 ins. diam., brs. S70½°W, 16.40 feet.

Blazed lines br. North and West.

Corner lies 100 feet South of metal fence post with location marker, which stands about 20 feet South of gravel road c. Southeast and Northwest.

March 11, 1987
R. Frost
D. Edwards

Edward McGinty
County Surveyor

V = 19¼°
P.-74