

## FIRST RE-ESTABLISHMENT

GCDB 200200

Section corner common to Sections 29, 30, 31 and 32, Township 34 South, Range 2 East, W.M.

Found at the corner position, exposed 6 ins., the 2½ ins. diam. galv. iron pipe with a 3½ ins. diam. brass cap set by the BLM in 1968, marked:

T34S R2E  
S30 | S29  
—+—  
S31 | S32  
1968

Original bearing trees recorded by Nathaniel Ford of the GLO in 1855, all sawed stumps, found and measured to center at base:

- Cedar, 37 ins. diam. brs. N35°E, 13.0 ft. record; 12.5 ft. to face.
- Fir, 38 ins. diam. brs. S24°W, 30.2 ft. record; 29.0 ft. to face.
- Fir, 38 ins. diam. brs. N29°W, 6.3 ft. record; 5.3 ft. to face.

Bearing trees recorded by the BLM in 1968, found with healed single blazes and measured to center at base:

- Sawed Fir stump brs. record; N11½°E, 37.0 ft.
- Fir, dead and down, brs. record; S21°E, 58.1 ft.
- Sawed Pine stump brs. record; S26°W, 37.0 ft.
- Sawed Fir stump brs. record; N45°W, 37.0 ft.

Mark new bearing trees "CS" "BT" and take measurements to center of trees at lower blaze:

- D. Fir 7 ins. diam. brs. N17°E, 16.2 ft.
- Cedar 7 ins. diam. brs. S59¼°E, 5.3 ft.
- D. Fir 8 ins. diam. brs. S44¼°W, 16.6 ft.
- D. Fir 7 ins. diam. brs. N83°W, 15.6 ft.

Corner lies approx. 850 ft. east of bend in Cobleigh Road.

April 19, 2011

H. Durkee

Kerry Bradshaw  
County Surveyor

P. – 63

V. – 16°50'