

FIRST RE-ESTABLISHMENT

GCDB 200340

Quarter corner common to Sections 19 and 20, Township 34 South, Range 2 East, W.M. $V = 20^\circ$

From the following evidence, at the location described below, I set a 1x36-inch G.I. pipe 30 ins. in the ground with a $2\frac{1}{2}$ ins. bronze disc marked:

Jackson County 1975
T34S R2E
 $\frac{1}{4}$ S
19 | 20

BTs recorded by N. Ford in 1855, found as follows:

- A White Oak, 16-inch diameter, scribed " $\frac{1}{4}$ " in partially exposed face, bears record N87°E, 5.28 feet. to scribed face.
- A stump depression, containing Pine remains, bears record S9°W, 33.0 feet.

I mound stones around corner, marked new trees C.S. BT and take measurements to center of trees at lower blaze:

- Douglas Fir, 16-inch diameter, bears N66½°E, 11.60 feet.
- Ponderosa Pine, 12-inch diameter, bears S16½°W, 14.40 feet.
- The corner, an 8-inch diameter Douglas Fir, of South and West bearing fence lines, bears S66°W, 12.70 feet.

Corner lies 75 feet North of the edge of clearing and 45 feet North of top of slope.

June 9, 1975
B. Malotte
R. Frost

Approved by: Edward McGinty
County Surveyor