

FIRST RE-ESTABLISHMENT

GCDB 200440

Quarter corner common to Section 17 and 18, Twp. 34 South, Range 2 East, W.M. $V = 21^\circ$

Reference: Filed Survey No. 2497, dated 1964.

Found, in mound of stone a $2\frac{1}{2}$ ins. O.D. iron pipe, projecting 41 ins., with welded cap marked:

18 | 17
R.S. 461

An original BT recorded by N. Ford in 1855, now a sawed Pine stump, about 27-inch diameter, scribed "BT" in opened lower face, bears record $S86^\circ W$, 335.28 feet to scribed face.

A probable original BT, a White Oak, 20-inch diameter, with exposed and rotted upper face, bears $N57\frac{1}{2}^\circ E$, 207.24 feet (on slope) to said face. Record: $N49^\circ E$, 207.24 feet.

BTs recorded on survey no. 2497 found as follows:

- Ponderosa Pine, 18-inch diameter, scribed "RS 461" and "BT" bears $S84\frac{1}{2}^\circ E$, 19.0 feet to center of tree at lower blaze.
- The Northerly fork, 12-inch diameter, of a double Black Oak, with scribe marks visible in partially healed blazes, bears $S7^\circ W$, 99.6 feet to center of tree at lower blaze.

I add the following marks to above noted cap:

T34S R2E
C.S.
1976

Corner lies on old, down, N-S rail fence in large brush field about 1,700 feet West of Cobleigh road.

February 3, 1976
Ed Graham
R. Frost

Approved by: Edward McGinty
County Surveyor