

FIRST RE-ESTABLISHMENT

GCDB 240300

Quarter corner between Sections 20 and 29. Township 34 South, Range 2 East.

Found original BT to Southeast with scribe marks legible; also, an oak to Northeast with scribe marks not in evidence, from which trees:

- Set a 1"x 36" gas pipe for corner.

From which:

- A 14" red fir scribed C.S.-BT bears N.67°30'W., 31.2 feet.
- A 10" cedar scribed C.S.-BT bears N.84°45'E., 74.6 feet.
- Set a ¾ x 14" pipe 30 feet West.

February 10, 1928
Boyden, Deputy County Surveyor
Byron Seaman and Bob Kent, Chainmen

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 240300

One-Quarter corner common to Sections 20 and 29, Township 34 South, Range 2 East, W.M.

From the following evidence of references recorded on First Re-establishment, page 1, in 1928, I set a 1x36-inch G.I. pipe, 5 ins. below the surface of and at the West edge of asphalt surface of Cobleigh Road, with 2½-inch diameter bronze disc for the corner marked:

JACKSON COUNTY

20
¼S —
29
1980

From which:

- Cedar, 18-inch diameter scribed "BT" in opened lower face bears N84°45'E (basis of bearing) 74.63 feet to scribed lower face. Record: N84°45'E, 74.6 feet.
- Fir snag, 24-inch diameter containing scribe marks in upper face, bears N69°15'W, 31.23 feet to partially exposed lower face. Record: N67°30'W, 31.2 feet.
- Found ¾-inch diameter iron pipe, flush with the surface of the ground, bears S87°23'W, 30.00 feet. Record: West 30 feet.

Note: The pipe with brass cap monument set by BLM in 1968 is found disturbed, bent and battered (apparently in maintenance and/or road (re) construction) nearby. The original position of this pipe bears approximately S72°W, 1.34 feet from the corner as determined from field references (1968) provided by C. Hurst (ORLS No. 483). Found BLM brass cap deposited alongside corner.

I set a 5/8 x 30 ins. rebar (on Northerly bearing right of way fence line) flush with the surface of the ground with yellow plastic cap marked: "JACKSON C.S." bears N17°35'W, 36.20 feet.

April 22, 1980
R. Frost
D. Danielsen

Approved by: Edward McGinty
County Surveyor