

FIRST RE-ESTABLISHMENT

GCDB 300240

Quarter Corner Sections 28 and 29. Township 34 South, Range 2 East.

Found the stumps of original trees with marks legible. Set rock with mound of rock about it for $\frac{1}{4}$ corner.

From which:

- A 40" White Oak bears S.13 $\frac{1}{2}$ °E., 124.5 feet.
- An 8" Black Oak bears S.69°W., 44.5 feet.

February 21, 1914
A.T. Brown,
Deputy County Surveyor

H. Ling, Chainman
P. Murphy, Chainman

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 300240

Quarter Section Corner 29 - 28, Township 34 South, Range 2 East.

Found the 11" Black Oak BT established by County Surveyor A.T. Brown February 21, 1914 with scribe legible. Also stump of the Southeast BT with scribe legible.

From which evidence:

- Set a 1"x36" galvanized iron pipe 18" in the ground and erected a mound of stone around said pipe for corner.

From which:

- The said 11" black oak bears South 71° West 44.5 feet;
- Scribe a 10" cedar CS-BT which bears South $63\frac{1}{2}^{\circ}$ West 21.3 feet;
- Scribe a 6" white oak CS-BT which bears North 36° West 28.7 feet.

October 29, 1954
C. Z. Boyden
Tom Furnas
M. E. Boyden

SEE NEXT PAGE FOR THIRD RE-ESTABLISHMENT

THIRD RE-ESTABLISHMENT

GCDB 300240

One-Quarter corner common to Sections 28 and 29, Township 34 South, Range 2 East, W.M.
 $V = 18\frac{3}{4}^\circ$

Found, at the corner the 1-inch diameter G.I. pipe projecting 14 ins. in mound of stone as set on Second Re-establishment, in 1954, page 4 of Jackson County Surveyors Records.

Inside of which I place and secure with cement a 3-inch diameter brass cap marked:

T34S R2E
29 | 28
¼S
CS
1980

From which I find bearing trees marked on above re-establishment and take measurements to center of trees at lower blaze:

- Incense Cedar, now 14-inch diameter with healed double blazes, bears $S63\frac{1}{2}^\circ W$, 21.40 feet. Record: $S63\frac{1}{2}^\circ W$, 21.3 feet.
- White Oak, now 8-inch diameter with healed double blazes bears $N36\frac{1}{2}^\circ W$, 28.62 feet. Record: $N36^\circ W$, 28.7 feet

I find bearing trees marked on First Re-establishment in 1914, page 1 of Jackson County Surveyors Records:

- Black Oak, now 12-inch diameter with healed double blazes, bears $S72^\circ W$, 44.75 feet to center of tree at lower blaze. 1914 Record: $S69^\circ W$, 44.5 feet 1954 Record: $S71^\circ W$, 44.5 feet.
- The Southeast bearing tree is dead and down at record location. 1914 Record: $S13\frac{1}{2}^\circ E$ 124.5 feet.

Corner lies in East-West bearing fence line.

May 14, 1980
J. Gallegos
B. Malotte

Approved by: Edward McGinty
County Surveyor