

FIRST RE-ESTABLISHMENT

GCDB 300400

Corner to Sections 16, 17, 20 and 21, Township 34 South, Range 2 East.

Found stone to mark corner which checks averages of distance of all four BTs.

Set a 2"x 36" galvanized pipe at exact location of stone.

From which:

- An 8" Black Oak scribed C.S. BT bears N28°30' W, 75.6 feet.
- A 14" Black Oak scribed C.S. BT bears S24°E, 71.8 feet.
- A 12" Black Oak scribed C.S. BT bears N62°0'E, 130.2 feet.
- The original BT a 30" White Oak bears S68°W, 167.5 feet.

February 3, 1931
C. Z. Boyden,
Deputy County Surveyor
Tice and Pettegrew, Chainmen

NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 300400

Section corner common to Sections 16, 17, 20 and 21, Township 34 South, Range 2 East, W.M.

Found at the corner position, exposed 6 ins. in a mound of stones the 2½-inch diameter galvanized iron pipe with a 3½-inch diameter brass cap set by the BLM in 1974, marked:

T34S	R2E
S17	S16

S20	S21
1974	

Original bearing trees recorded by Nathaniel Ford of the GLO in 1855, found and measured to center of root holes:

- Rotted Oak remains br. Record: N37°E, 34.3 feet.
- Oak, dead down and rotted bears Record: S30°E, 33.0 feet.

Bearing trees recorded on First Re-establishment in 1931, found with healed double blazes and measured to center at base:

- Oak, dead down and rotted bears Record: N62°E, 130.7 feet.
- Black Oak, now 16-inch diameter bears N28°W, 75.9 feet. Record: N28½°W.

Bearing trees recorded by the BLM in 1974, found with healed single blazes and measured to center at base:

- White Oak, now 10-inch diameter bears Record: S51°E, 54.8 feet.
- White Oak, now 6-inch diameter bears Record: S44°W, 51.5 feet.

Bearing tree recorded on Survey No. 9202 in 1981, a White Oak 13-inch diameter with healed double blazes bears N43°E, 79.8 feet. Record: N42°20'E, 79.5 feet.

Note: Mushroomed 2-inch diameter galvanized iron pipe set on said First Re-establishment is exposed 3 ins. and bears west, 0.3 feet.

Corner lies approximately 850 feet north of gravel road.

April 20, 2011

H. Durkee

Kerry Bradshaw

Jackson County Surveyor

P. – 64

V. – 15°20'