


FIRST RE-ESTABLISHMENT


GCDB 400140

Quarter Corner common to sections 33 and 34, Township 34 South, Range 2 East, W.M.
Found the 5/8-inch diameter rebar with 1-inch diameter aluminum cap mkd;



Set on filed Survey No. 6458, dated 1976, protruding 2 inches above small mound of stone.

Set a 1 x 30-inch flanged galvanized iron pipe with 2-inch diameter brass cap mkd;



Over found monument and build large mound of stone flush to brass cap.

Bearing trees marked by Nathaniel Ford in 1855 found;

- Black Oak 16-inch diameter, hollow and sawed open, bears record S71°E, 7.92 feet to estimated face.
- Black Oak, dead and down shell, bears record N51°W, 21.12 feet to root hole.

Trees marked on Survey no. 6458 found;

- White Oak 5-inch diameter with healed single blaze bears N69°E, 5.02 feet to center of tree at base. Record N75¾°E, 4.9 feet.
- White Oak 6-inch diameter with healed single blaze bears N26°W, 35.84 feet to center of tree at base. Record N23¼°E, 35.5 feet.

Mark a new tree 'CS BT' and measure to the center of tree at lower blaze;

- Ponderosa Pine 13-inch diameter bears S01°W, 35.62 feet.

Corner is located in rock outcrop on spur ridge course E-W. A blazed and painted line runs West from corner.

February 22, 2001

S. Beecher

T. Newcomb

Roger Roberts

County Surveyor

P.-10

V=15°