

FIRST RE-ESTABLISHMENT

GCDB 400598

Closing Corner common to Sections 3 and 10 on the East boundary of Section 9, Township 34 South Range 2 East, W.M.

Found 5/8-inch diameter rebar with 1-inch diameter aluminum cap marked:

RS 461
9 | 3 C
—
10 C

Inside of a 1x36-inch Galvanized iron pipe and flush in a mound of stone.

Remove found rebar and pipe and set a 1x 36-inch Galvanized iron pipe with 2½-inch diameter press fit brass cap marked:

JACKSON COUNTY 1908
T34S R2E
9 | 3 C
—
10 C

Flush in mound of stone.

From which:

- A stone set by Eugene B. Henry in 1908 bears East 8.60 feet.
- An original bearing tree marked by Henry in 1908 found.
- Douglas Fir 48-inch diameter with healed double blazes bears N50°E, 56.61 feet to the center of tree at base.

Bearing trees marked on Survey No. 3022 dated 1966 found and measured to the center of tree at base:

- White Fir 11-inch diameter, with healed single blaze bears N40°E, 34.73 feet. Record distance 35.3 feet.
- Douglas Fir 14-inch diameter, with healed single blaze, bears S52°E, 26.12 feet. Record S50°E, 26.3 feet.
- Douglas Fir snag 24-inch diameter, with healed single blaze, bears N67°W, 15.40 feet. Record N70°W, 16.0 feet.

Corner lies at the East edge of clear-cut and approximately 400 feet South of dirt road.

January 8, 1998

S. Beecher

T. Newcomb

Roger Roberts

County Surveyor

V = 17½°

P. -1

Search Coordinates: 42°38'06"
122°34'41"