

FIRST RE-ESTABLISHMENT

GCDB 440300

Quarter corner common to Sections 22 and 27, Township 34 South, Range 2 East, W.M.

Found at the corner position, exposed 4 inches in a mound of stones, the 2½-inch diameter galvanized iron pipe with a 3½-inch diameter brass cap set by the BLM in 1968, marked:

T34S R2E
S22
¼S —
S27
1968

Original bearing trees recorded by Eugene Henry of the GLO in 1908, found and measured to center of trees at base:

- Fir snag with scribe marks "4SBT" in opened blaze bears Record: N31½°E, 9.9 feet.
- Rotted, sawed pine stumps bear Record: S4½°E, 33.0 feet.

Bearing trees recorded by the BLM in 1968, sawed fir stumps, found and measured to center at base:

- Douglas Fir with healed single blaze bears Record: N2½°W, 40.3 feet.
- Douglas Fir with chopped-out face bears S75°W, 39.9 feet. Record: 40.3 feet.

Mark new bearing trees "CS" "BT" and take measurements to center of trees at lower blaze:

- Douglas Fir 8-inch diameter bears N86°W, 10.2 feet.
- Douglas Fir 10-inch diameter bears N80¾°E, 15.5 feet.
- Douglas Fir 8-inch diameter bears S66°E, 30.6 feet.
- Madrone 13-inch diameter bears S29¾°W, 28.3 feet

Corner lies approximately 400 feet northwesterly from dirt logging road.

April 7, 2008

H. Durkee

B. Beeman

Roger R. Roberts

Jackson County Surveyor

P. - 66

V. - 16°10'