

**FIRST RE-ESTABLISHMENT  
CLOSING CORNER TO SECTIONS 2 AND 3 ONLY  
GCDB 500700**

Closing corner between Sections 2 and 3, Township 34 South, Range 2 East, W.M.

At the closing corner, found (tipped over) the original 21x15x4 inches stone marked with 2 notches on the East and 4 on the West side and "CC" on top.

Replace said stone with and deposited it alongside a 1x36-inch Galvanized iron pipe, set flush with the ground, with a 2½ inches bronze cap marked:

JACKSON COUNTY 1981  
T34S R2E  
S3 | S2  
C.C.

Original bearing trees marked by E. B. Henry in 1908 found:

- Fir stump shell, approximately 48-inch diameter, bears S56°E, 62.7 feet (on slope) to estimated location of original face. Record: S53°E, 62.7 feet.
- White Fir, 16-inch diameter, containing scribe marks including "S" in partially exposed face bears Record: S41°30'W, 14.52 feet to scribed face.

Mark a new tree "CS" "BT":

- White Fir, 9-inch diameter, bears S38°07'E, 59.17 feet to center of tree at lower blaze.
- A bearing tree referencing a closing corner monument, (described below) recorded as "on line" (township) on Survey No. 3022, dated 1966;
- A White Fir, now dead, 9-inch diameter with healed single blaze, bears N32°12'W, 33.35 feet to center.

A found rebar, 5/8-inch diameter with aluminum cap marked:

"34"  
—  
3 | 2  
C.C.  
RS461

Flush with the ground set on above survey, bears S0°05'E, 3.70 feet.

From said rebar, previously described bearing trees measured as follows:

- Original (1908) SW BT; S33°30'W, 17.46 feet to scribed face. Record (survey No. 3022) S35°W, 17.9 feet.
- Survey No. 3022 BT; N36°W, 30.3 feet to center. Record: 30.7 feet.

Corner lies about 340 feet N45°W of location marker on 19-inch diameter Cedar located alongside "B" Road c. Northeast.

April 28, 1981  
R. Frost  
R. Templin

Edward McGinty  
County Surveyor

V = 16°  
P. -70