

FIRST RE-ESTABLISHMENT

GCDB 600140

Quarter corner common to Section 35 and 36, Twp. 34 South, Range 2 East, W.M. $V = 21\frac{3}{4}^\circ$

Found, the single remaining bearing tree recorded by N. Ford in 1855, now a sawed madrone stump, 33-inch diameter, containing reverse impression of scribed "S".

From the preceding evidence I set a 1x36-inch G.I. pipe 30 inches in the ground with a 2½ inches bronze disc marked:

Jackson County 1977
T34S R2E
¼S
35 | 36

From which, the above-described original bearing tree bears Record: $S25^\circ E$, 22.44 feet to scribed (reverse) face.

I mark the following new trees CS BT and take measurements to center of trees at lower blaze:

- Douglas fir, 9-inch diameter, bears $S77\frac{1}{2}^\circ E$, 20.13 feet
- Douglas fir, 10-inch diameter, bears $S4\frac{1}{2}^\circ W$, 26.25 feet.
- The center, at outlet end invert, of a 18-inch diameter C.M.P. bears $S7^\circ W$, 15.80 feet.

Corner lies on East slope, 27 feet East of road, $C.N7^\circ W$.

November 1, 1977

B. Malotte

R. Frost

A. Rambo - MedCounty Corp.

Approved by: Edward McGinty
County Surveyor

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 600140

Quarter corner common to Sections 35 and 36 of Township 34 South, Range 2 East, W.M.

Found at corner position exposed 4 inches, the 1-inch diameter galvanized iron pipe with a 2½-inch diameter brass cap set on First Re-establishment in 1977 and marked:

JACKSON COUNTY 1977
T34S R2E
¼ S
35 • 36

Single remaining original bearing tree recorded by N. Ford of the GLO in 1855 found, a madrone now a rotted stump bears S 27° E, 23.5 feet to center of stump. Record: S25°E, 22.4 feet to face.

Bearing trees recorded on First Re-establishment found with healed double blazes and measured to center at lower blaze:

- Douglas Fir now 23-inch diameter bears Record: S77½°E, 20.1 feet.
- Douglas Fir now 19-inch diameter bears Record: S4½°W, 26.3 feet.

Marked new bearing tree "CS" "BT" and measured to center at lower blaze:

- Madrone 6-inch diameter bears N31°E, 13.8 feet.

Put punch mark in top of outlet of an 18-inch diameter corrugated metal culvert bears S7°W, 16.80 feet.

Corner lies approximately 20 feet east of gravel logging spur road.

December 13, 2007

B. Beeman

H. Durkee

Roger R. Roberts

Jackson County Surveyor

P - 257

V - 16°0'