

## FIRST RE-ESTABLISHMENT

GCDB 600300

Section corner common to Sections 23, 24, 25 and 26 of Township 34 South, Range 2 East, W.M.

Found at corner position exposed 4 ins. in a mound of stones, the 2½ ins. diam. galv. iron pipe with a 3½ ins. diam. brass cap set by the BLM in 1968 and marked:

T34S R2E  
S23 | S24  
—+—  
S26 | S25  
1968

MEDCO monument alongside exposed 8 ins., a 1½ diam. galv. iron pipe with a 2 ins. diam. threaded cap marked:

S23      S24  
MEDCO  
S26      S25

Original bearing trees recorded by Eugene B. Henry of the GLO in 1908 found and measured to center at base:

- Fir 36 ins. diam. snag with a healed single blaze brs. N30½°E, 28.4 ft. Record; 27.7 ft.
- S. pine 73 ins. diam. snag with a partially healed upper blaze with "4 S" brs. record; S24½°W, 87.1 ft.

Bearing trees recorded by the BLM in 1968 found with healed single blazes and measured to center at base:

- W. fir now 28 ins. diam. brs. record; S19½°E, 64.0 ft.
- W. fir now blown down brs. record; N25°W, 33.7 ft. to center of stump hole.

Marked new bearing trees "CS" "BT" and measured to center at lower blaze:

- D. fir 15 ins. diam. brs. N30¼°E, 14.6 ft.
- Shasta red fir 15 ins. diam. brs. S54½°W, 64.1 ft.
- D. fir 9 ins. diam. brs. N41¼°W, 47.5 ft.

Corner lies approx. 1450 ft. southerly along closed spur road.

June 18, 2008

B. Beeman

H. Durkee

Roger R. Roberts

Jackson County Surveyor

P. – 119

V. – 16°55'