

**FIRST RE-ESTABLISHMENT  
 CLOSING CORNER TO SECTIONS 1 AND 2 ONLY  
 GCDB 600700**

Closing Corner common to Sections 1 and 2 only, Township 34 South, Range 2 East, W.M.  
 V=13°

At the corner, found disturbed, the original 12x9x6 inches stone; record 15x8x6 ins., marked with 5 grooves and "CC" on adjacent sides.

Replace found stone with and deposit it alongside a 1x36-inch G.I. pipe set 30 inches in the ground with a 2½-inch diameter bronze disc marked:

JACKSON COUNTY 1980  
 T33S R2E  
 35  
 ———  
 S2 | S1  
 CC  
 T34S

From which:

- An original bearing tree recorded by E. Henry in 1908, now a Fir stump, 14-inch diameter
- Scribed "SR2E S2" in partly exposed single face, bears Record: S78°W, 12.54 feet to scribed face.
- The stump hole, of a down White Fir, 14-inch diameter containing scribed "SR2" in partly exposed face bears record (1908): S18°E, 7.92 feet.

A found 5/8-inch diameter rebar projecting 2 inches with aluminum cap marked:

RS461  
 35  
 ———  
 C2 | C1

Bears, as recorded on Survey No. 3355, dated 1967, North, 3.80 feet.

- The Southwest reference tree to above rebar, marked in 1967, is now gone.

Reference trees (to above rebar) scribed in 1970 (reference survey No. 4179) found as follows and measurements taken from re-established (brass cap) 1908 closing corner.

- White Fir, 10-inch diameter with scribe marks visible in partially exposed single face, bears S56°E, 30.85 feet to center of tree at base.
- White Fir, 12-inch diameter, with scribe marks visible in partially exposed single face, bears S85°W, 29.57 feet to center of tree at base.

Mark a new tree "CS" "BT":

- White Fir, 13-inch diameter, bears South 25.45 feet to center of tree at lower blaze.

Corner lies about 65 feet North of road.

September 15, 1980  
 R. Frost  
 Witness: T. Newcomb, USFS

Edward McGinty  
 County Surveyor

P. -185