

FIRST RE-ESTABLISHMENT

GCDB 700100

Township corner to Township 34 South, Ranges 2 and 3 East, and Township 35 South, Ranges 2 and 3 East.

Found the basalt corner stone. Also the Northeast BT with the scribe legible. The BT blaze was found intact which scribe had 98 growth rings over the scribe. Also found stump holes which agree with Northwest and Southeast BTs.

From which evidence:

- Set a 2"x 36" galvanized iron pipe 18" in the ground for corner.
- Placed the 6" x 12" x 15" basalt stone alongside the pipe

From which pipe for corner:

- A 6" Douglas Fir scribed CS-BT bears S.5°E., 19.2 feet;
- The original BT now a 10" Douglas Fir with the original scribe bears N.8°E., 17.9 feet;
- Scribe a 28" Black Oak CS-BT which bears N.68°W., 31.3 feet;
- Scribe a 6" White Fir CS-BT which bears S.74°W., 23.2 feet.

July 29, 1955
C. Z. Boyden
E. W. Smith

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT
GCDB 700100

Township Corner to Townships 34 & 35 South, and Ranges 2 & 3 East, W.M.
Found at the corner position, exposed 10 ins., the 2½ ins. diam. galv. iron pipe with a 3½ ins. diam. brass cap set by the BLM in 1957 and marked:

T34S
R2E R3E
S36 | S31
—+—
S1 | S6
T35S
1957

2½ ins. diam. galv. iron pipe exposed 18 ins. brs. West 0.4 ft.

Original bearing tree recorded by R. Moore of the GLO in 1883 found, but not measured;

- Fir rotted blow-down and buried under large pile of blown-down trees

Bearing trees recorded on 1st re-establishment in 1955 found with healed double blazes and measured to center at lower blaze;

- D. fir now 13 ins. brs. record S5°E, 19.1 ft.
- Fir blow down brs. record S74°W, 23.1 ft. to center of stump hole.
- Oak blow down brs. record N68°W, 31.0 ft. to center of stump hole.

Marked new bearing trees 'CS''BT' and measured to center at lower blaze;

- Madrone 9 ins. diam. brs. S51°W, 24.2 ft.
- D. fir 12 ins. diam. brs. N17°W, 23.4 ft.

Due to large pile of blow-down, no tree accessible in the North-East quadrant

Corner lies approx. 1100 ft. east of logging road near top of ridge in blow-down area

July 22, 2009

B. Beeman
H. Durkee

Kerry K. Bradshaw
Jackson County Surveyor

P. -157
V. - 12°15'