

**FIRST RE-ESTABLISHMENT
CLOSING CORNER TO SECTIONS 13 AND 24 ONLY
GCDB 700400**

Closing corner for Sections 13 and 24, Township 34 South, Range 2 East, W.M.

Found at the corner position, exposed 6 ins. in a mound of stones, the 2 ins. diam. galv. iron pipe with a 2½ ins. diam. brass cap set on Survey No. 9201 in 1981, marked:

T34S T34S
CC S13 | R3E
S24 | S19
R2E
1981
RPLS 601

Original stone found in mound of stones.

Bearing trees recorded on Survey No. 2770 in 1965, found and measured to center at base:

- Rotted fir stob with scribe marks "461" on exposed face, brs. record; S61°W, 38.9 ft.
- Cedar, now 8 ins. diam. with healed double blazes, brs. N16½°W, 16.3 ft. Record; N25½°W, 17.2 ft.

Bearing tree recorded on Survey No. 9201 in 1981:

- A rotted fir stob, brs. record; S34°W, 24.4 ft. to center at base.

Take new reference:

- D. Fir 10 ins. diam. with 3 hack marks on northeast side and a "K" tag dated 1964, brs. S42½°W, 5.5 ft. to center at base.

Corner lies approx. 800 ft. east of a logging road.

February 7, 2011

H. Durkee

Kerry Bradshaw
Jackson County Surveyor

P. – 22

V. – 14°10'