

FIRST RE-ESTABLISHMENT

GCDB 100500

Corner common to Sections 7 and 18, Township 35 South, Range 2 West and Sections 12 and 13, Township 35 South, Range 3 West.

Set a 1" x 36" galvanized iron pipe 28" in the ground with a 2½" bronze cap stamped:

T35SR2&3W	
12	7
SEC	COR
13	18
C.S.	
1967	

From which:

- A 14" Black Oak with BT scribe bears South 73½° West, 33.0 feet to face of the upper blaze;
- The center of a Black Oak shell snag bears North 36½° West, 84.8 feet;
- The center of a rotted Oak stump bears South 11° East, 38.4 feet;
- Also found stump hole and some remains of a rotted Pine for the Northeast tree.

Marked the following new trees:

- A 13" Fir scribed CS-BT bears South 68° West, 29.1 feet to the face of the upper blaze;
- An 18" Pine scribed CS-BT bears North 35° West, 34.0 feet to the face of the lower blaze;
- A 5" White Oak scribed CS-BT bears South 78° East, 19.6 feet to the face of the lower blaze;
- A 10" Laurel scribe CS-BT bears North 64¼° East, 45.2 feet to the face of the lower blaze.

December 5, 1967
F.A. Roberts, J. Huston

Approved By:
L. D. Pinkham
Deputy County Surveyor

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 100500

Section corner common to Sections 7 and 18, Township 35 South, Range 2 West and Sections 12 and 13, Township 35 South, Range 3 West, W.M.

Found firmly set, projecting 7 ins., the 1 in. diam. galvanized iron pipe with 1967 Jackson County brass cap marked:

T35S	
R2 & 3W	
12	7

13	18
C.S.	
1967	

As recorded on First re-establishment, page 30, in 1967.

Bearing trees reported in 1967, now dead and burned, found:

- Madrone, 10 ins. diam., with scribed "S" visible in partly exposed upper face, brs. N65°E, 45.7 feet to center of tree at lower blaze. Record; N64¼°E, 45.2 feet to lower face.
- White Oak, 7 ins. diam., with healed blazes brs. S78°E, 20.0 feet to center of tree at lower blaze. Record; S78°E, 19.6 feet to lower face. (Basis of Bearing)
- All other bearing trees of record have been destroyed in recent forest fire.

Take new references:

- Steel fence post, 2½ ins. diam., being the corner of North & East bearing fence lines, brs. N30°E, 8.25 feet to center at base.

Rebars, 5/8 x 24 ins. projecting 3 ins. with Jackson County metal caps br.:

- N27°W, 25.83 feet with steel fence post alongside.
- S28°E, 21.23 feet with steel fence post alongside.
- S30°W, 18.52 feet with steel fence post alongside.

Corner lies about 50 feet easterly of private drive to residence 11376 Ramsey Road at end (p.t.) of sharp, right hand curve, near ostrich pens.

October 19, 1994
Ron Frost, Tech.
Tom Newcomb, Tech.

Verlyn Thomas
County Surveyor

V = 19½
P.-141