

**SECOND RE-ESTABLISHMENT
GCDB 200140**

Quarter corner Sections 31 and 32, Township 35 South, Range 2 West.

Found

- A ¾" iron pipe set for corner also original BT to Southwest, plainly scribed.
- Also stump hole to Southeast which agree with the official government record.

Set a 1" x 36" galvanized iron pipe 36" in the ground to replace the said ¾" iron pipe

From which:

- An 18" Black Oak scribed CS-BT bears S19°W, 18.05 feet;
- Scribe a 6" Black Oak CS-BT which bears N56°E 20.9 feet;
- A 15" Black Oak with two blazes bears S41½°E.

February 4, 1949
C. Z. Boyden
L. D. Pinkham
G. L. Ray

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 200140

Quarter corner common to Sections 31 and 32, Township 35 South, Range 2 West, W.M.

Found flush, the 1 ins. diam. iron pipe reported set on first re-establishment, page 18, in 1949. In the top of said pipe, set in concrete, a 2½ ins. diam. brass cap marked:

T35S R2W
¼S
31 | 32
C.S.
1988

Original bearing tree marked by Ives and Hyde in 1854 found:

- Black Oak, now 42 ins. diam. with rotted interior visible, brs. Record: S13°W, 93.47 feet to center of tree at root crown. Record distance; 93.06 feet to face.

Bearing trees marked on said first re-establishment found with double healed blazes and measured to center of trees at lower blaze:

- Black Oak, now 12 ins. diam. brs. Record: N56°E, 20.85 feet. Record distance; 20.9 feet.
- Black Oak, now 26 ins. diam., brs. Record: S19°W, 18.80 feet. Record distance; 18.05 feet.

Corner lies under a north-south fence, 4.0 feet South of a corner post to fences east-west and south and about 50 feet South of the south edge of a large opening.

April 26, 1988
D. Edwards, Tech.
T. Newcomb, Tech.

Edward McGinty
County Surveyor

V = 18¼°

P. - 171