

FIRST RE-ESTABLISHMENT

GCDB 200400

Section corner common to Sections 17, 18, 19, and 20, Township 35 South, Range 2 West, W.M.
 $V = 20\frac{1}{2}^\circ$

From evidence and at the location noted below, I leaded a $\frac{3}{4}$ x 12 ins. re-steel rod in a 3 ins. deep hole drilled in rock. I attached a center punch (otherwise unmarked) $2\frac{1}{2}$ ins. bronze disc

From which:

- The foot of a sandstone ledge, noted by Ives and Hyde in 1854 as lying .10 chains North of corner, bears North, 6.2 feet.
- The perpendicular face of a sandstone ledge bears as recorded in 1854, $N77^\circ E$.
- An original BT, a White Oak, now 18 ins. diam., containing scribed "BT", bears $N56^\circ W$, 94.3 feet to scribed face. Record, $N56^\circ W$, 89.56 feet.

I mound stone around corner, marked a new tree C.S. BT and set the following reference objects:

- A 1 ins. P.K. nail with metal disc, set in face of vertical sandstone bluff (approximately 18 feet high) bears $N66^\circ E$, 12.40 feet.
- A $\frac{5}{8}$ x 17 ins. re-steel rod set 13 ins. in a sandstone crevice bears $S45\frac{1}{2}^\circ W$, 15.52 feet.
- A 1 ins. P.K. nail, with metal disc, set in sandstone face, bears West, 20.13 feet.
- A White Oak, 8 ins. diam., bears East, 74.7 feet to center of tree at lower blaze.

November 19, 1973

R. Frost

O. Frederick

Approved by: Edward McGinty
County Surveyor

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 200400

Section corner common to Sections 17, 18, 19 and 20, Township 35 South, Range 2 West, W.M.

Found at the corner, the $\frac{3}{4}$ in. diam. iron rod in drill hole described in first re-establishment, dated 1973. $2\frac{1}{2}$ ins. diam. bronze disc, recorded as set atop said iron rod, on first re-establishment destroyed. Replace said disc with a $2\frac{1}{2}$ ins. diam. brass cap, set in concrete, marked:

JACKSON COUNTY 1990
T35S R2W
18 | 17
—+—
19 | 20
C.S.

Single remaining original bearing tree and topography calls recorded by Ives and Hyde in 1854, found:

- White Oak, now 18 ins. diam., with exposed faces and containing faint scribe marks "BT", brs. N56°W, 94.8 feet to center of tree at base. Record: 89.56 feet to face.
- Foot of sandstone ledge, brs. North 6.2 feet. Record: 0.10 chain.
- Perpendicular face of sandstone ledge brs. Record: N77°E.

References set on first re-establishment, found:

- $\frac{5}{8}$ ins. diam. re-bar in sandstone crevice brs. Record: S45½°W, 15.52 feet.
- "PK" nail in 1 in. diam. metal disc, in vertical sandstone face, brs. Record: West, 20.13 feet.
- White Oak, now 9 ins. diam., brs. East, 74.5 feet to center of tree at lower blaze. Record: 74.7 feet.

Mark new tree "CS" "BT":

- A Pine, 6 ins. diam. brs. S65°W, 29.6 feet to center of tree at lower blaze.

Corner lies on bare rock slope, about 6 feet South of vertical sandstone face and West, about 70 feet of ravine, c. South.

November 20, 1990
H. Durkee, Tech.
T. Newcomb, Tech.

Verlyn Thomas
County Surveyor

V = 18½°
P.-140