

FIRST RE-ESTABLISHMENT

GCDB 200540

Quarter corner common to Sections 7 and 8, Township 35 South, Range 2 West, W.M. $V=22^\circ$

From the original evidence and at the location described below I set a 1 x 36 ins. G.I. pipe 32 ins. in the ground with a $2\frac{1}{2}$ ins. bronze disc marked:

T35S R2W
¼S
7|8
C.S.
1973

Original BTs recorded by Ives and Hyde in 1854 were found as follows:

- A Yellow Pine stump, containing scribed "BT" bears record, $N58^\circ E$, 8.58 feet.
- A Yellow Pine stump, bears $S47^\circ W$, 11.22 feet Record, $S42^\circ W$, 11.22 feet.
- A stump hole found at record location of line tree noted by Ives and Hyde, South, 11.22 feet.

I mound stone around corner, marked a new tree and the following references:

- A hub tack, set in lead, in the center of a chiseled "X" on the high point of a 4 x 11 feet rock outcrop, exposed 1.3 feet, bears $S74^\circ E$, 41.52 feet.
- A Cedar, 19 ins. diam., marked C.S. BT bears $N04^\circ 30' W$, 41.6 feet to center of tree at lower blaze.

Corner lies approximately 40 feet East of stream.

Posted a location marker on S. Pine along East side of power line clearing approximately 75 feet West of corner.

December 3, 1973

E. Graham

B. Malotte

Approved by: Edward McGinty
County Surveyor