

FIRST RE-ESTABLISHMENT

GCDB 200600

Corner common to Sections 5, 6, 7, and 8 Township 35 South Range 2 West.

Set a 1" x 36" galvanized iron pipe for corner,

From which:

- The original witness tree (now a 36" Y Pine stump with scribe marks plain) bears North 27° West, 49.2 feet;
- The original witness tree (now a Black Oak stump) bears North 44½° East, 36.3 feet;
- The original witness tree (now a 14" White Oak intact) bears South 59° East, 48.8 feet;
- The original witness tree (now a 15" Black Oak intact) bears South 12° West, 21.6 feet.

I mark new witness trees as follows:

- A 5" Fir, scribed "CS-BT" bears South 66° West, 14.4 feet;
- A 6" Fir, scribed "CS-BT" bears North 15¾° West, 29.1 feet;
- A 6" Fir, scribed "CS-BT" bears North 86½° East, 11.9 feet;
- A 5" White Oak, scribed "CS-BT" bears South 40° East, 39.0 feet.

October, 1960
F.A. Roberts
O. Blankenship

Approved By:
Mark E. Boyden
Deputy County Surveyor

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 200600

Section corner common to Sections 5, 6, 7 and 8, Township 35 South, Range 2 West, W.M.

Found projecting 3 ins., the 1 ins. diam. iron pipe reported set on first re-establishment, page 21, in 1960.

Original bearing trees marked by Ives and Hyde in 1854 found:

- Rotted Pine snag, 21 ins. diam. and containing scribe marks including "2W T35S S6" brs. Record: N27°W, 49.0 feet to said face. Record distance; 48.84 feet.
- White Oak, now 15 ins. diam. with healed blazes, brs. S59°E, 49.2 feet to center of tree at root crown. Record: S58°E, 48.84 feet to face.
- Black Oak, now 15 ins. diam. with rotted interior, brs. S12°W, 22.0 feet to center of tree at root crown. Record: S14°W, 21.12 feet to face.

Bearing trees marked on said first re-establishment found with double healed blazes and measured to center of tree at lower blaze:

- Douglas Fir, now 13 ins. diam. brs. Record: N86½°E, 11.9 feet.
- White Oak, now 7 ins. diam., brs. Record: S40°E, 39.0 feet.
- Douglas Fir, now 9 ins. diam., brs. S68°W, 14.80 feet. Record: S66°W, 14.40 feet.
- Douglas Fir, now 11 ins. diam., brs. record N15¾°W, 29.50 feet Record distance; 29.1 feet.

Corner lies on 13% East slope, in trees and an estimated 70 feet south and 750 feet east of pole number DF-P10 on a high tension line bearing Northeast and Southwest.

April 25, 1988
D. Edwards, Tech.
T. Newcomb, Tech.

Edward McGinty
County Surveyor

V = 17°

P.-169

SEE NEXT PAGE FOR THIRD RE-ESTABLISHMENT

THIRD RE-ESTABLISHMENT

GCDB 200600

Section corner common to Sections 5, 6, 7 and 8, Township 35 South, Range 2 West, W.M.

Found projecting 5 ins., the 1 ins. diam. galvanized iron pipe set on first re-establishment, dated 1960. On the top of found pipe set a 2½ ins. diam. brass cap marked:

T35S R2W	
6	5

7	8
C.S.	
1994	

Single remaining bearing tree recorded by Ives and Hyde in 1854 found burned 15 ins. diam. oak snag brs. record (1988); S59°E, 49.20 feet to center at base.

Bearing trees marked on first re-establishment, dated 1988, and re-described on second re-establishment found and measured to the center of tree at lower blaze:

- Burned fir snag, 13 ins. diam., brs. N86½°E, 12.15 feet. Record: 11.90 feet.
- Burned fir snag, 12 ins. diam., brs. S66°W, 14.65 feet. Record: S68°W, 14.80 feet.
- Burned oak snag, 7 ins. diam., brs. Record: S40°E, 39.00 feet.
- Burned fir snag, 10 ins. diam., brs. Record: N15¾°W, 29.50 feet.

New references set, 5/8x24 ins. diam. rebar with aluminum caps marked "Jackson County CS" and directly behind references set a small 36 ins. long metal fence post with location tag attached:

- Projects 4 ins., N36½°W, 22.78 feet.
- Projects 2 ins., N39½°E, 25.20 feet.
- Projects 3 ins., S37°E, 18.52 feet.
- Projects 6 ins., S39°W, 24.62 feet.

Corner lies 400 feet east of newly built road. Posted location tag on a 14 ins. diam. Douglas Fir at east edge of road.

October 5, 1994
T. Newcomb, Tech.
R. Frost, Tech.

Verlyn Thomas
County Surveyor

V = 17°
P.-152