

FIRST RE-ESTABLISHMENT

GCDB 200640

Quarter Corner to Sections 5 and 6, Township 35 South, Range 2 West, W.M.

Found the line tree North 25.1 feet, also both bearing trees down with old ax marks (no scribe visible); from which evidence set a 1" x 36" galvanized pipe 30" in the ground for corner

From which:

- A 12" black oak scribed CS-BT bears S71°E 4.2 feet.
- Scribed a 6" red fir CS-BT which bears N38°W26.4 feet.

November 25, 1946
C. Z. Boyden
L. D. Pinkham

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 200640

Quarter corner to Sections 5 and 6, Township 35 South, Range 2 West, W.M.

Found flush, the 1 ins. diam. iron pipe reported set on first re-establishment, page 18, in 1946. In the top of said pipe, set in concrete, a 2½ ins. diam. brass cap marked:

T35S R2W
¼S
6+5
C.S.
1988

Original bearing trees marked by Ives and Hyde in 1854 found:

- Stump hole, with axed and rotted Pine remains alongside, brs. S46½°E, 57.3 feet to estimated center of hole.
- Stump hole, with rotted Pine remains alongside, brs. N44°W, 29.3 feet to estimated center of hole.
- Stump hole of original line tree, with rotted Pine remains alongside, brs. N1°W, 27.0 feet to estimated center of hole.

Bearing trees marked on said first re-establishment found:

- Black Oak, now 14 ins. diam. with double healed blazes, brs. S73¾°E, 4.43 feet to center of tree at lower blaze.
- Douglas Fir, now 16 ins. diam. with scribed "CS" visible in exposed upper face, brs. Record: N38°W, 26.8 feet to center of tree at lower blaze.

Corner lies in trees on gentle North slope, about 700 feet West from a large carport.

April 21, 1988
D. Edwards, Tech.
T. Newcomb, Tech.

Edward McGinty
County Surveyor

V = 17°
P.-165

SEE NEXT PAGE FOR THIRD RE-ESTABLISHMENT

THIRD RE-ESTABLISHMENT

GCDB 200640

Quarter corner common to Sections 5 and 6, Township 35 south, Range 2 West, W.M.

Found flush, the 2½ ins. diam. brass cap set on second re-establishment, dated 1988 and marked:

T35S R2W
¼S
6+5
C.S.
1988

Bearing trees reported on second re-establishment found and measured to center of tree at lower blaze:

- Sawed Douglas Fir, 18 ins. diam., brs. Record: N38°W, 26.80 feet.
- Black Oak, 15 ins. diam., with healed blazes, brs. S72°E, 4.43 feet. Record: S73¾°E.

Marked new tree "CS" "BT":

- Cedar, 9 ins. diam., brs. S16°W, 83.04 feet to the center of tree at lower blaze.

5/8 ins. diam. x 24 ins. rebar with aluminum caps marked "Jackson County CS":

- brs. S16°W, 40.35 feet.
- brs. S16°W, 62.20 feet.

Area has been burned over and logged.

Corner lies at north edge of jeep road.

February 3, 1997
T. Newcomb, Tech.
K. Harper

Roger Roberts
County Surveyor

P.-12