

FIRST RE-ESTABLISHMENT

GCDB 200700

Section Corner on Township Line - Sections 31 & 32, Township 34 South, Range 2 West and Sections 5 & 6, Township 35 S, Range 2 West.

Found remains of old stake for corner, the original black oak bearing tree to southwest in good condition, original bearing tree snag to southeast with scribe legible, also stumps of bearing trees to northwest and northeast.

Replaced corner stake with 2" x 36" galvanized iron pipe for corner (33" in the ground),

From which:

- The original bearing tree, a 26" black oak plainly scribed, bears S. 42° W. 48.8 feet.
- Scribed an 18" fir C.S. - BT which bears N43°W 2.7 feet.
- Scribed an 18" fir C.S. - BT which bears S2¾°E 57.2 feet.
- Scribed an 18" fir C.S. - BT which bears S77½°E 40.5 feet.

May 10, 1944
C. Z. Boyden
J. H. Cushman

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 200700

Section corner common to Sections 31 and 32, Township 34 South, Range 2 West, and Sections 6 and 5, Township 35 South, Range 2 West, W.M.

At the corner found projecting 7 ins. the 2 ins. diam. iron pipe with 3 ins. diam. standard BLM brass cap marked:

	T34S	
S31		S32

S6		S5
T35S R2W		
1959		

- The 2-inch diameter iron pipe set on First Re-establishment, page 14 in 1944 (apparently removed by the BLM) is found projecting 15 inches along east side of corner.
- An original bearing tree, recorded by Ives & Hyde in 1854, a Black Oak, now 29 inches in diam. with re-healed blazes, bears Record: S42°W, 48.84 feet to estimated face. Re-measured 49.5 feet to center of tree.
- Bearing tree marked on First Re-establishment found: Fir snag, 22-inch diameter with healed blazes, bears Record: N43°W, 2.7 feet to estimated face. Re-measured 3.25 feet to center of tree.

BLM bearing trees found and measured to center of trees:

- Fir snag 23-inch diameter with scribe marks visible in partly exposed faces, bears N4°30'E, 57.70 feet. Record: N2°E, 58.08 feet.
- Fir stob, 11-inch diameter, containing (partial) scribed "T35S R2W S6 BT" in single exposed face, bears S40°50'W, 42.10 feet. Record: S40°W, 41.58 feet.
- Fir stump, 17-inch diameter containing scribed "BT", bears N83°W, 31.5 feet. Record: N84°W, 31.02 feet.

Mark new trees "CS" "BT" and take measurements to center of trees at lower blaze:

- Black Oak, 6-inch diameter, bears N27°45'E, 42.70 feet.
- White Oak, 5-inch diameter, bears S48°E, 83.80 feet.
- White Oak, 6-inch diameter, bears S57°W, 9.00 feet.
- White Oak, 7-inch diameter, bears N69°15'W, 34.00 feet.

Corner lies on nearly level ground, at the North edge of sparsely wooded opening. Recent blazed line (BLM) brs. North from corner.

April 16, 1985
R. Frost
B. Rodgers

Edward McGinty
County Surveyor

V = 20°

P. -186