

FIRST RENEWAL

GCDB 300400

Corner common to Sections 16, 17, 20 and 21, Township 35 South Range 2 West.

Chiseled a cross on a large sandstone ledge for corner, from which:

- The original witness tree (now a Y. Pine stump with "BT" scribe marks plain) bears North $73\frac{1}{2}^{\circ}$ West, 33.7 feet;

I mark new witness trees as follows:

- A 10" Laurel, scribed "CS-BT" bears South 21° East, 10.0 feet to the face of the upper blaze;
- A 6" Black Oak, scribed "CS-BT" bears North $70\frac{1}{2}^{\circ}$ West, 18.9 feet to the face of the lower blaze;
- A 10" Black Oak, scribed "CS-BT" bears South 65° West, 26.7 feet to the face of the lower blaze.

March 13, 1962

F. A. Roberts

L. Hart

Approved By:

Mark E. Boyden, County Surveyor

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 300400

Section corner common to Sections 16, 17, 20 and 21, Township 35 South, Range 2 West, W.M.

At the corner, found large chiseled cross in sandstone outcrop, set on first re-establishment, page 24 in 1962. In the center of found cross, set P-K nail flush.

An original bearing tree recorded by Ives & Hyde in 1854, now a Pine stump core about 10 ins. diam. containing scribed "BT", brs. record N73½°W, 33.66 feet to scribed face.

Bearing trees marked on first re-establishment found:

- Madrone, 15 ins. diam. scribed "CS" "BT" in exposed faces, brs. S21°E, 9.90 feet to scribed upper face. Record 10.0 feet. Re-measured to center of tree at lower blaze, 10.10 feet.
- Black Oak, 13 ins. diam. with healed blazes, brs. S65°W, 27.25 feet to center of tree at lower blaze. Record: 26.7 feet.
- Black Oak, 10 ins. diam. with healed blazes, located on fence line c. S50°E, brs. N70½°W, 19.0 feet to center of tree at lower blaze. Record: 18.9 feet.

Corner lies on steep East slope, about 20 feet west of the top of (70%) slope and 2 feet North of fence line C. Southeast.

August 18, 1983
E. McGinty
R. Frost

Edward McGinty
County Surveyor

V = 18½°
P.-83

SEE NEXT PAGE FOR THIRD RE-ESTABLISHMENT

THIRD RE-ESTABLISHMENT

GCDB 300400

Section corner common to Section 16, 17, 20 and 21, Township 35 South, Range 2 West, W.M.

Found p-k nail, in center of "X" chiseled into a sandstone outcrop, as set on the Second re-establishment page 56 in 1983.

Remove P-K nail and set a 2½ ins. diam. brass cap marked:

T35S R2W	
17	16
20	21
C.S.	
1989	

in cement in hole drilled in center of "X".

From which the remains of an original bearing tree marked by Ives & Hyde in 1854;

- Pine stump core with "BT" scribe visible brs. record: N73½°W, 33.7 feet.

Bearing trees marked on the First re-establishment page 24 in 1962 found and re-measured on the Second re-establishment:

- Madrone 14 ins. diam. with "CS BT" scribe visible on partially healed blazes brs. record S21°E, 10.1 feet bearing taken to upper face.
- Black Oak 14 ins. diam. with healed blazes brs. record S65°W, 27.2 feet.
- Black Oak 10 ins. diam. with healed blazes brs. record N70½°W, 19.0 feet.

Mark a new tree "CS BT" and measure to center of tree at lower blaze:

- Douglas Fir 11 ins. diam. brs. N26¼°E, 34.8 feet.

Corner lies on East slope 2.5 feet North of a fence line bearing N70°W.

August 31, 1989
S. Beecher
T. Newcomb

Verlyn Thomas
County Surveyor

V = 16°
P.-183