

FIRST RE-ESTABLISHMENT

GCDB 300500

Section corner to Sections 8, 9, 16, 17, Township 35 South, Range 2 West.

Found the BT scribe visible on the Southeast BT now a laurel stump; also, the snag of the Southwest BT badly burned; no scribe visible.

Found stump holes for evidence of the other two original BTs from which evidence set a 1" x 36" galvanized iron pipe with a 1½" expander filled with pot metal and stamped:

T35S, R2W	
8	9
— —	
17	16
C.S.	
1957	

and set 31" in the ground for corner

From which:

- A 14" cedar scribed C.S.-BT bears South 60° East 23.1 feet.
- Scribed an 11" S. Pine C.S.-BT which bears North 88½° East 19.4 feet.
- Scribed a 6" Douglas Fir C.S.-BT which bears North 21½° East 16.9 feet.
- Scribed a 10" Douglas Fir C.S.-BT which bears North 57° West 28.8 feet.

October 27, 1957
C. Z. Boyden
Bob Vincent

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 300500

Corner common to Sections 8, 9, 16 and 17, Township 35 South, Range 2 West, W.M.

Found projecting 2 ins. in a mound of stones, the 1x36 ins. iron pipe with lead filled expander as described on first re-establishment, page 19, in 1957.

Replaced said pipe with a 1x36 ins. galvanized iron pipe set 28 ins. in the ground. In the top of said pipe, set in concrete, a 2½ ins. brass cap marked:

T35S R2W
8 | 9
—+—
17 | 16
C.S.
1988

Rebuild mound of stones around pipe.

Original bearing trees marked by Ives and Hyde in 1854 found:

- Madrone remains brs. S80°E.
- Burnt Pine stump brs. S33°W, 35.1 feet to approximate center.

Bearing trees marked on said first re-establishment found with double healed blazes and measured to center of trees at lower blaze:

- Douglas Fir, now 9 ins. diam., brs. Record: N21½°E, 17.18 feet. Record distance; 16.9 feet.
- Sugar Pine, now 16 ins. diam., brs. N85½°E, 19.67 feet. Record: N88½°E, 19.4 feet.
- Cedar, Now 21 ins. diam., brs. S59¼°E, 23.75 feet. Record: S60°E, 23.1 feet.
- Douglas Fir, now 15 ins. diam., brs. Record: N57°W, 29.18 feet. Record distance; 28.8 feet.

Corner lies in timber on a 30%, S76°W slope, an estimated 450 feet West from a location poster on a 10 ins. diam. Fir snag on the West side of a dirt road, course North-South.

April 28, 1988
D. Edwards, Tech.
T. Newcomb, Tech.

Edward McGinty
County Surveyor

V = 17½°

P.-179