

FIRST RE-ESTABLISHMENT

GCDB 340400

Quarter Corner to Sections 16 and 21, Township 35 South, Range 2 West, W.M.

Found

- Original BT to northeast with scribe visible;
- Also stump which corresponds to original BT to southwest.

Set a 1" x 30" iron pin 22" in the ground for corner,

From which:

- A 12" white oak scribed C.S.-BT bears N.29½°E., 52.1 feet.
- Scribed a 7" white oak C.S.-BT which bears S.81½°E., 55.9 feet.

November 29, 1944

C. Z. Boyden

B. L. Campbell

R. E. Welch

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 340400

Quarter corner common to Sections 16 and 21, Township 35 South, Range 2 West, W.M.

Found projecting 8 ins., a $\frac{5}{8}$ ins. diam. iron pin (record 1 ins. diam.), reported set on first re-establishment, page 10, in 1944.

Replace said pin with, and deposit alongside of, a 1 x 36 ins. galvanized iron pipe set 24 ins. in the ground. In the top of said pipe, set in concrete, a $2\frac{1}{2}$ ins. diam. brass cap marked:

T35S R2W
16
 $\frac{1}{4}$ s —
21
CS
1988

Original bearing tree marked by Ives and Hyde in 1854 found:

- Black Oak, now 19 ins. diam. with rotted lower and healed upper blaze, brs. Record: N7°E, 23.55 feet. to center of tree at root crown.
- No evidence of other original bearing tree.

Bearing trees marked on said first re-establishment found with double healed blazes and measured to center of trees at lower blaze:

- White Oak, now 15 ins. diam., brs. Record: N29 $\frac{1}{2}$ °E, 53.0 feet. Record distance; 52.1 feet.
- White Oak, now 9 ins. diam., brs. S80°E, 55.9 feet. Record bearing; S81 $\frac{1}{2}$ °E.

Corner lies at the easterly terminus of a line of steel fence posts which brs. West on a brushy, 20%, S45°W slope.

April 28, 1988
D. Edwards, Tech.
T. Newcomb, Tech.

Edward McGinty
County Surveyor

V = 19°
P.-178