

## FIRST RE-ESTABLISHMENT

GCDB 400340

Quarter Corner to Sections 21 and 22, Township 35 South, Range 2 West, W.M.

Found original white oak BT to northeast with BT scribe legible.

From which evidence

- Set a 1" x 35" iron pipe 18" in the ground for corner,

From which;

- A 12" twin white oak scribed C.S.-BT bears S.81 $\frac{3}{4}$ °W., 49.1 feet.
- Scribed a 14" white oak C.S.-BT which bears N.23 $\frac{3}{4}$ °E., 109.5 feet.

**Note:** Dug hole and set mound of stone around pipe below the surface of the ground.

September 2, 1944  
C. Z. Boyden  
B. L. Campbell  
L. J. Shorey

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

## SECOND RE-ESTABLISHMENT

### GCDB 400340

Quarter corner common to Section 21 and 22, Twp. 35 South, Range 2 West, W.M.  $V = 19\frac{1}{2}^\circ E$

Found the 1 inch iron pipe as set by County Surveyor in the first re-establishment in 1944, exposed 13 ins., from which: an original BT, 26 ins. diam., White Oak with axed open and rotted faces, bears  $N30^\circ E$ , 48.8 feet to face of lower blaze. Record,  $N37^\circ E$ , 95.7 feet.

The BTs marked in the first re-establishment found as follows:

- Twin White Oak, 18 ins. diam., with healed blazes, bears record  $S81\frac{3}{4}^\circ W$ , 49.1 feet to estimated face of lower blaze.
- White Oak, 15 ins. diam. with healed blazes, bears record  $N23\frac{1}{4}^\circ E$ , 109.5 feet to estimated face of lower blaze.

According to the first re-establishment narrative, the pipe was set at record from the original N.E. BT. Due to the large discrepancy between record and existing measurements to the tree, a search of the records was made and the following observations noted.

- In the field notes of the first re-establishment, the corner was described as being the " $\frac{1}{4}$  cor. of Section 15 and 16, T35S, R2W." At apparently a later date "15 & 16" were crossed out and "21 & 22" penciled in above them.
- A check of the records of the  $\frac{1}{4}$  cor. of Section 15 and 16 shows one of its original BTs as being a "White Oak..., bears  $N30^\circ E$ , 74 lks." 74 links equals 48.8 feet
- It is apparent that the information for the  $\frac{1}{4}$  cor. of Section 15 and 16 was used to re-establishment this corner.

To correct this, I set a 1 x 36 ins. G.I. pipe, exposed 13 ins. with a  $2\frac{1}{2}$  ins. bronze disc marked:

Jackson County 1976  
T35S R2W  
 $\frac{1}{4}$ S 21 | 22

At record from the original BT.

The original BT now bears  $N37^\circ E$ , 95.7 feet to face of lower blaze.

The BTs marked by the County Surveyor in 1944 are as follows:

- White Oak, 15 ins. diam., bears  $N30^\circ E$ , 155.6 feet to center of tree.
- White Oak, 18 ins. diam., bears  $N30\frac{1}{4}^\circ W$ , 33.5 feet to center of tree. **Note:** the blazes on this tree do not face the true corner.
- The found 1 inch iron pipe bears  $N43\frac{1}{4}^\circ E$ , 47.55 feet.

The true corner is in a mound of stone, 31 feet South and 24 feet East of the intersection of a North-South and East fences.

October 6, 1976  
R. Roberts  
Ed Graham

Approved by: Edward McGinty  
County Surveyor